



MTM5000 SERIES TETRA TWO-WAY MOBILE RADIO

The MTM5000 Series TETRA mobile radios are sleek and durable and packed with features that have become essential for safe and effective operations. These include End-to-End Encryption and features that enable ease of operation in the most demanding situations such as high audio quality, high receiver sensitivity, an intuitive keypad, and a high-definition colour display.

The MTM5000 series mobile radios support a wide range of applications and installation options including: fixed control room, vehicle, motorcycle and custom installation.

MTM5000 SERIES BENEFITS

















- Extended Operational Range
- Superior Audio Performance
- Low User Migration Costs
- Enhanced End-to-End Encryption Options
- Location Services
- Advanced Terminal Management
- Flexible Installation Options
- Rugged Design with Exceptional Reliability



MTM5000 SERIES SPECIFICATIONS



	MTM5200	MTM5400	MTM5500
MODELS - COMPLIANT WITH DIN 75490 (ISO 7736)			
Dash	Compact radio for fast vehicle installation		N.A.
Desk	Compact radio, for use in the office. Optional range of accessories such as desk tray with integrated loudspeaker		N.A.
Multiple Remote Control Head	N.A.		Radio with multiple remote mount control head capability
	N.A.		Range of installation options enable use in cars, vans and other vehicles
Multiple Transceiver or Control Head	N.A.	Radio with multiple remote mount control head capability	Range of installation options enable use in cars, vans and other vehicles
Motorcycle	Environmentally enhanced radio meeting IP67 specification. Suitable for demanding environments such as motorcycle, fire appliance and marine installations		N.A.
Expansion head "Databox"	Radio without a control head, for data applications, or customised application development		

GENERAL										
		MTM5200	Dimensions H x W x D (mm)	Weight Typical (g)	MTM5400	Dimensions H x W x D (mm)	Weight Typical (g)	MTM5500	Dimensions H x W x D (mm)	Weight Typical (g)
Dash / Desk Mount	Transceiver & Control Headhead)		60 x 188 x 198	1,500		60 x 188 x 198	1,300	N.A.		
	Dash / Desk Control Head		60 x 188 x 31	230		60 x 188 x 31	1,070	N.A.		
Remote Mount	Transceiver & Expansion Head		45 x 170 x 185	1117		45 x 170 x 185	230		45 x 170 x 196	1330
	Remote Control Head		60 x 188 x 39	300		60 x 188 x 39	300		60 x 188 x 39	330
	IP67 Control Head		60 x 188 x 39	320		60 x 188 x 39	320	N.A.		
	Telephone Style Control Head	N.A.			N.A.				220 x 65 x 75	450 (excluding cable)
Databox	Transceiver & Expansion Head		45 x 170 x 194	1201		45 x 170 x 194	1201		45 x 170 x 196	1330

USER INTERFACE & DISPLAY		
Display	Diagonal dimension	2.8"
	Type	VGA - 640x480 pixels, 65,000 colours
	Backlight	Variable backlight, User configurable
	Font sizes	Standard & Zoom mode (90 pixels, 4.5mm high) characters
TSCH		N.A.
Buttons & Keypad	Numeric	Integral backlit numeric keypad of 12 keys, with keypad lock option
	International keypad versions ¹	Roman, Arabic, Cyrillic, Korean, Chinese, Taiwanese characters
	Programmable function keys	3 programmable function keys (plus 10 programmable numeric keys)
	Navigation	4-way navigation key, menu and soft keys
	Emergency	Emergency button with backlight
Rotary	Dual Function	User configurable shortcuts to menus and common features using "One-Touch-Button" feature
Indication	LED	Talkgroup and volume change with lock option
	Tones	Tri-colour LED
User Interface Languages	Standard Options	Configurable notification tones
	User defined	Arabic, Chinese Simplified, Chinese Traditional, Croatian, Danish, Dutch, English, French, German, Greek, Hebrew, Hungarian, Italian, Korean, Lithuanian, Macedonian, Mongolian, Norwegian, Portuguese, Russian, Spanish, Swedish
Menu		User programmable, using ISO 8859-1 character
		Tailored to user needs
		Menu Shortcuts
Contacts Management		Menu Configuration
Contact List		Cellular Type
		Up to 1,000 contacts
Multiple Dialling Methods		Up to 6 numbers per contact, Max 2,000 numbers
Fast/Flexible Call Response		User selects how to dial
Multiple Ring Tones		Private Call Response to a Group Call via One Touch Button
Message Manager		Configurable with CPS
Text message list		Cellular Type
Intelligent Keypad Text Input		20
Status list		All Control Heads
Country/Network Code List		400
Scan lists		100
Discrete Mode		40 lists of 20 groups
Screen Saver		All Control Heads
Universal Time Display		gif image & text (any user's selection)
Keypad Lock		All Control Heads
Talkgroup Folders		All Control Heads
		Dual layer folder structure (folder/subfolder)
Favourite Folders		256 folders
		Up to 3 (to store any favourite talkgroup)

¹ For availability of other language keypads please contact your local Motorola Solutions representative

MTM5000 SERIES SPECIFICATIONS

		MTM5200	MTM5400	MTM5500
ELECTRICAL SPECIFICATIONS				
Voltage Range		10.8 to 15.6 V DC		
Current Consumption (A, typ.)	Idle / Rx / Tx @ 10W	N.A.	0.5 / 1.0 / 1.2 (TX 3.4A Peak)	
	Idle / Rx / Tx @ 3W		0.5 / 1.0 / .9 (TX 2.2A Peak)	
	Tx - Multi Slot PD (4 slots) @ 5.6W	N.A. (3W only)	2.7	
	Using USB host		Adds 0.5A	
RF SPECIFICATIONS				
Frequency Bands (MHz)		350 - 390, 380 - 430, 410 - 470, 806 - 870		
Transmitter RF Power	TETRA Release 1	N.A. (3W only)	10W (Class 2) and 3W (Class 3)	
RF Power Control	6 Power Step Levels (steps of 5 dBm)	Starting at 15 dBm; finishing at 40 dBm		
Receiver Class		A & B		
Receiver Static Sensitivity (dBm)		-114 minimum, -116 typical (ETSI 300-392-2)		
Receiver Dynamic Sensitivity (dBm)		-105 minimum, -107 typical (ETSI 300-392-2)		
GNSS SPECIFICATIONS				
Simultaneous Satellite Systems		GPS plus one other GNSS, eg GLONASS, BeiDou		
Mode of Operation		Concurrent tracking, SBAS capable, 72 channel		
GNSS Antenna		Supports active antenna (5V, 25mA supply)		
Acquisition Sensitivity		-145 dBm (guaranteed); -146 dBm (typical)		
Tracking Sensitivity		-162 dBm (guaranteed); -163 dBm (typical)		
Horizontal Accuracy, 2D		5m (95% probable) @ -130dBm		
Location Protocols		ETSI Location Information Protocol (LIP)		
		Motorola LRRP		
ENVIRONMENTAL SPECIFICATIONS				
Operating Temperature (°C)		-30 to +60		
Storage Temperature (°C)		-40 to +85		
Not in use - Storage	ETSI 300 019-1-1 CLASS 1.3	Non-Weather Protected Storage Locations		
Not in use - Transportation	ETSI 300 019-1-2 CLASS 2.3	Public Transportation		
Stationary use - Weather Protected Locations	ETSI 300 019-1-3 CLASS 3.2	Partly Temperature Controlled Locations		
Mobile use - Ground Vehicle Installation	ETSI 300 019-1-5 CLASS 5.2	Climatic Tests		
Mobile use - Ground Vehicle Installation	ETSI 300 019-1-5 CLASS 5M3	Mechanical Tests		
Rail Certification Environmental	EN50155:2007 and IEC60571 ED.3.0	Environmental		
MIL STD	810 C/D/E/F/G Specifications	All 11 categories met (or exceeded)		
Dust and Water Ingress Protection	IP54 (dust cat. 2)	Dash/Desktop/Remote models		
	IP67	Motorcycle model (only control head is IP67; transceiver is IP54)		MTM5500 TSCH IP55
VOICE SERVICES				
Talkgroups		10,000 TMO, 2,000 DMO		
Phone book entries		1,000 persons. Up to 6 numbers per entry (mobile, office etc). Max 2,000 entries		
Scan lists		40 lists of 20 talkgroups		
Trunked Mode (TMO) Services	Group call	Late Entry, TMO/DMO Mapping		
	Private call	Half / Full Duplex		
	Telephony (PABX, PSTN, MS-ISDN)	Full Duplex		
	DGNA	Up to 10,000 groups		
	Scanning	Attachment signalling, supports SWMI initiated attachment/detachment		
Direct Mode (DMO) Services		Group call		
Emergency (tailored by users)		Private call		
	Tactical	Emergency Group Call to ATTACHED talkgroup		
	Non-Tactical	Emergency Group Call to DEDICATED talkgroup		
	Individual	Emergency Call to PREDEFINED party (half/full duplex)		
	Smart emergency	TMO to DMO and DMO to TMO automatic switching options		
	Hot Mic	Configurable timers for automatic open mic (talk without PTT)		
	Location	Location (GPS) sent with emergency		
	Target Address	Sent to individual or group address (selected or dedicated)		
	Alarm (status message)	Emergency Status (or other pre-defined status)		
DATA SERVICES				
Status	Alias messages	400 Entries		
	Options	Can be sent via One-Touch or via menu		
Short Data Service (SDS)	Inbox/Outbox	Up to 200 Entries (short messages) At least 20 Entries for Outbox (long messages) ² At least 10 Entries for Inbox (long messages) ²		
	Predictive Text	Cellular style iTAP predictive text entry		
	Target Address	Sent to individual or group address (selected or dedicated)		
	Voice Call Interaction	SDS messages can be sent and received during a voice call		
Packet Data (PD)	Multi-slot PD	Data transmission with up to 4 slots supporting up to 28.8 kbit/s gross		
WAP	Integrated WAP browser (including WAP-PUSH)	Integrated Openwave browser		
		WAP 1.2.x and WAP 2.0 compatibility for UDP/IP Stack		
Peripheral Equipment Interface (PEI)	Interface Protocol	AT Commands - Full Set ETSI Mandatory Compliant		
		AT Multiplexer - 4 Virtual Physical Port (simultaneous PD, SDS, AT commands and Air Tracer SESSIONS)		
Terminal Management		TNP1; enables simultaneous PD and SDS sessions		
		Programmable via Motorola Integrated Terminal Management (iTM) solution		

² Long messages of up to 1,000 characters

MTM5000 SERIES SPECIFICATIONS

		MTM5200	MTM5400	MTM5500
GATEWAY SERVICES				
DMO/TMO Gateway		N.A.	Group voice calls from DMO to TMO	
		N.A.	Group voice calls from TMO to DMO	
		N.A.	Emergency group call from DMO to TMO	
		N.A.	Emergency group call from TMO to DMO	
		N.A.	Call Pre-emption (in either direction)	
		N.A.	SDS messaging through the gateway from DMO to TMO or TMO to DMO	
		N.A.	Configurable routing of SDS messages to console or PEI ³	
		N.A.	Point to point calls and SDS messages whilst operating as a Gateway	
REPEATER SERVICES				
DMO Repeater		N.A.	Repeats DMO voice calls on selected talkgroup	
		N.A.	Repeats SDS and Status messaging on selected talkgroup	
		N.A.	ETSI type 1A DMO Repeater for channel efficient operation	
		N.A.	Transmission of Repeater Presence Signal	
		N.A.	Priority Call	
		N.A.	Emergency Call (Pre-emptive Priority Call)	
		N.A.	E2EE Encrypted DMO traffic	
		N.A.	Monitoring of and participation in calls whilst in Repeater mode	
	N.A.	Configurable Repeater Power Levels		
INTERFACES				
RS232		Four Virtual Ports via AT Multiplexer enable PC applications to run simultaneously Packet Data, AT Commands, SDS, SCOUT		
USB			USB 2.0 support for PEI (Two Virtual Ports via standard Windows drivers enable PC applications to run simultaneously Packet Data and AT Commands)	
			USB 2.0 support for PEI (Four Virtual Ports via AT Multiplexer enable PC applications to run simultaneously Packet Data, AT Commands, SDS, SCOUT); rapid programming	
			USB On-The-Go (host & slave) capability for intelligent PEI applications	
			USB 1.1 support (Host Mode) to manage USB Slave Devices (e.g. SIM CARD READER)	
Rugged Accessory Connector (GCAI)		GCAI - Motorola accessory and ancillary interface for connection of accessories, data terminals and programming		
General Purpose Input/Output	Digital I/O	7 (4 on remote and motorcycle control head, 3 on transceiver)		
	Analog input	4 (1 on remote and motorcycle control head, with 4 levels)		
SECURITY FEATURES				
Air Interface Encryption	Algorithms	TEA1, TEA2, TEA3		
	Security Classes	Class 1 (Clear), Class 2 (SCK), Class 3G		
	Authentication	Infrastructure initiated and made mutual by terminal		
Provisioning		Secure provisioning tool via Key Variable Loader (KVL)		
User Access Control		PIN/PUK code access		
	Service Profile Selection for Radio User Assignment / Radio User Identity (RUA/RUI) Operation	Based on login credentials, a radio user can be limited to only those radio capabilities defined in pre-installed service profiles, selected by the infrastructure		
Data		Packet Data user authentication		
End to End Encryption (E2EE)	Voice E2EE	Enhanced End-to-End Encryption with OTAR supported through Universal Crypto Module (UCM) and SIM (via integrated card slot) and or Cryptr 2 Broadband IP unit.		
	Packet Data E2EE			
	Short Data (SDS) E2EE			
REGULATORY COMPLIANCE				
Radio (RED Article 3.2)		EN 302 561		
EMC (R&TTE Article 3.1.b)			EN 301 489-1	
			EN 301 489-18	
Electrical Safety (R&TTE Article 3.1.a)			EN 60950-1	
			EN50360 EME	
Environmental			WEEE Directive	
			EN50155 (IEC 60571 ED. 3.0)	
Automotive	E-mark, ECE Regulation No.10 for Electrical/Electronic-Subassembly			
Rail Certification EMC	EN50121-3-2 (IEC 62236-3-2 Ed 2.0)			

³ Future software release

For more information, please visit: motorolasolutions.com/MTM5000

Specifications are subject to change without notice.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2021 Motorola Solutions, Inc. All rights reserved. (01-21)