



**DIGITAL, NOW WITHIN REACH**

# MOTOTRBO™ DP2000 SERIES DIGITAL TWO-WAY PORTABLE RADIOS



Monitoring supply needs on a manufacturing line or reporting an incident on a construction site, how do you keep employees connected and safe? MOTOTRBO digital radio solutions can help by putting the power of digital communications within reach.

Versatile and powerful, MOTOTRBO combines the best of two-way radio functionality with the latest digital technology. DP2000 Series radios offer best-in-class audio in a scalable solution to meet your communication needs. Because they are also analogue interoperable, you can make the transition to digital at your own pace and budget.

The DP2000 Series radios can remaster your workplace and the way people collaborate to help you achieve even greater productivity, safety and cost-effectiveness.

## INDUSTRY-LEADING AUDIO

When it comes to exceptional audio clarity, the quality of digital can't be denied. With the DP2000 Series portables, you get digital quality throughout your coverage area plus unique features to help your employees hear and speak clearly, wherever they work.

With Intelligent Audio, the radio volume automatically adjusts to compensate for background noise. Now, workers don't have to adjust their radio volume to avoid missing a call in loud situations or disturbing others when they move into quiet places. Increased background noise suppression filters out unwanted external clamour – from the rumble of forklifts to the buzz of traffic noise. And IMPRES™ audio accessories enhance noise suppression and improve voice intelligibility for smarter audio than they've ever experienced before.

## HIGH-POWERED PERFORMANCE

Because the DP2000 Series uses TDMA digital technology, it delivers twice the calling capacity plus clearer voice communications. When it comes to battery performance, these radios operate up to 40 percent longer between recharges compared to analogue. In fact, the leading-edge IMPRES™ technology in our batteries, chargers and audio accessories also ensures longer talk time and clearer audio.

The DP2000 Series offers plenty of features to make workers more efficient. Voice announcement provides audible confirmation so they can be notified of channel and zone changes as well as programmable button features without having to view the radio display. The display and easy to use navigation menu makes the radio intuitive to use so they can stay focused on the job at hand - from the hotel receptionist confirming rooms to security covering a sporting event.

## MIGRATE AT YOUR OWN PACE

Keeping operations running smoothly during a change in communication systems is vital to your operation. It's easy to migrate to digital because the DP2000 Series radios operate in analogue and digital mode while the dynamic mixed mode repeater functionality streamlines automatic switching between analogue and digital calls. So you can begin using MOTOTRBO radios and repeaters on your existing analogue system, and when your time and budget allow, move to digital at your own pace.

## DAY-IN, DAY-OUT DURABILITY

The DP2000 Series meets demanding specs, including IP55 for water protection and U.S. Military Standard 810 C, D, E, F and G. DP2000 radios have a two-year Standard Warranty with 1-year warranty for batteries and accessories. In addition, Service from the Start provides multi-year peace of mind with fast repair turnaround times, expert telephone technical support and access to the latest software releases<sup>1</sup>; all backed by Motorola's globally integrated services infrastructure, highly qualified support technicians and certified repair facilities.



## DP2000 SERIES SPECIFICATIONS

GENERAL SPECIFICATIONS*					
		DISPLAY DP2600		NON DISPLAY DP2400	
		VHF	UHF	VHF	UHF
Channel Capacity		128	128	16	16
Frequency		136-174MHz	403-527 MHz	136-174 MHz	403-527 MHz
IMPRES Hi-Cap Li-ion (2250 mAH) Battery	Height (H)	122 mm		122 mm	
	Width (W)	56 mm		56 mm	
	Thickness (T)	41.7 mm		41.7 mm	
	Weight	305 g		285 g	
IMPRES Li-ion Slim (1600mAH) Battery	Height (H)	122 mm		122 mm	
	Width (W)	56 mm		56 mm	
	Thickness (T)	36.4 mm		36.4 mm	
	Weight	285 g		285 g	
Power Supply		7.5 V (Nominal)			
Operating Temperature		-30°~ +60 °C <sup>2</sup>			
Average battery life		5/5/90 duty cycle with carrier squelch and transmitter in high power <sup>3</sup>			
IMPRES Hi-Cap Li-ion (2250 mAH) Battery		Analogue: 11.5 hrs / Digital: 16.5 hrs		Analogue: 11.5 hrs / Digital: 16.5 hrs	
IMPRES Li-ion Slim (1600 mAH) Battery		Analogue: 8 hrs / Digital: 11.5 hrs		Analogue: 8 hrs / Digital: 11.5 hrs	

\*Availability subject to country law and regulations. Specifications subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements.

MILITARY STANDARDS											
		810C		810D		810E		810F		810G	
APPLICABLE MIL-STD	METHOD	PROCEDURES	METHOD	PROCEDURES	METHOD	PROCEDURES	METHOD	PROCEDURES	METHOD	PROCEDURES	
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II	
High Temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.5	I-A1, II	
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I-C3, II/C1	502.5	I, II	
Temperature Shock	503.1	-	503.2	I/A1/C3	503.3	I/A1/C3	503.4	I	503.5	I-C	
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I	505.5	I-A1	
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.5	I, III	
Humidity	507.1	II	507.2	II	507.3	II	507.4	-	507.5	II	
Salt fog	509.1	-	509.2	-	509.3	-	509.4	-	509.5	-	
Dust	510.1	I	510.2	I	510.3	I	510.4	I	510.5	I	
Vibration	514.2	VIII/F, Curve-W	514.3	I/10, II/3	514.4	I/10, II/3	514.5	I/24	514.6	I-cat 24, II/5	
Shock	516.2	I, II	516.3	I, IV	516.4	I, IV	516.5	I, IV	516.6	I, IV, VI	

## PRODUCT SPEC SHEET

### MOTOTRBO™ DP2000 SERIES PORTABLE RADIOS

RECEIVER		
	VHF	UHF
Frequencies	136-174 MHz	403-527 MHz
Channel Spacing	12.5/20/25kHz	
Frequency Stability	± 0.5 ppm	
Analogue Sensitivity (12dB SINAD) Typical	0.3uV 0.22uV (typical)	
Digital Sensitivity	0.25 uV (0.19 uV typical)	
Intermodulation (TIA603D)	70 dB	
Adjacent Channel Selectivity (TIA603A)-1T	60dB @ 12.5kHz / 70dB @ 20/25kHz	
Adjacent Channel Selectivity (TIA603D)-2T	45dB @ 12.5kHz / 70dB @ 20/25kHz	
Spurious Rejection (TIA603D)	70 dB	
Rated Audio	0.5W	
Audio Distortion @ Rated Audio	5% 3% (typical)	
Hum and Noise	-40dB @ 12.5kHz / -45dB @ 20/25kHz	
Audio Response	TIA603D	
Conducted Spurious Emission (TIA603D)	-57 dBm	

ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature	-30° C / +60 °C <sup>2</sup>
Storage Temperature	-40° C / +85 °C
Thermal Shock	Per MIL-STD
Humidity	Per MIL-STD
ESD	IEC 61000-4-2 Level 3
Dust and Water Intrusion	IEC60529 - IP55

Testing completed using portable radio with attached battery and antenna.

TRANSMITTER		
	VHF	UHF
Frequencies	136-174 MHz	403-527 MHz
Channel Spacing	12.5/20/25kHz	
Frequency Stability	± 0.5 ppm	
Low Power Output	1W	1W
High Power Output	5W	4W
Modulation Limiting	± 2.5 kHz @ 12.5 kHz	
	± 4.0kHz @ 20 kHz	
	± 5.0 kHz @ 25 kHz	
FM Hum and Noise	-40 dB@ 12.5 kHz	
	-45 dB @ 20/25 kHz	
Conducted/Radiated Emission	-36 dBm < 1 GHz	
	-30 dBm > 1 GHz	
Adjacent Channel Power	60 dB @ 12.5 kHz	
	70 dB @ 20/25 kHz	
Audio Response	TIA603D	
Audio Distortion	3%	
4FSK Digital Modulation	12.5kHz Data: 7K60F1D & 7K60FXD	
	12.5kHz Voice: 7K60F1E & 7K60FXE	
	Combination of 12.5 kHz Voice and Data: 7K60F1W	
Digital Vocoder Type	AMBE+2™	
Digital Protocol	ETSI TS 102 361 -1,-2,-3	

<sup>1</sup> Software release covers patches and maintenance releases of the current version to the operating system i.e. that shipped with the terminal.

<sup>2</sup> Radio only - Li-Ion battery -10C

<sup>3</sup> Actual battery runtime observed may vary based on the specific radio configuration.

For more information on how to strengthen your mobile voice, visit [motorolasolutions.com/mototrbo](http://motorolasolutions.com/mototrbo)

#### Motorola Solutions Australia Pty Limited

The information presented herein is to the best of our knowledge true and accurate. No warranty or guarantee expressed or implied is made regarding the capacity, performance or suitability of any product. MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylised M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2012 Motorola Solutions, Inc. All rights reserved. BTB/MA673 05/14

**MOTOTRBO**  
DIGITAL  
REMASTERED.

