



MISSION READY WHEN IT MATTERS MOST

APX™ 2000 PROJECT 25 PORTABLE RADIO

Chemical spill. Catastrophic storm. Power outage. When every minute matters, you must communicate instantly with other agencies and responders. But how do you prepare for a disaster and keep control of operating costs? That's where the APX 2000 P25 portable radio answers the call, expertly and affordably.

The APX 2000 delivers all the benefits of TDMA technology in the smallest P25 capable portable in the industry. Easy to use, tough as nails, a hard value to beat, it seamlessly connects agencies throughout your city for fast, interoperable communications.

EVERY INCH AN APX

The APX 2000 leverages the leading attributes of the APX family of P25 TDMA portables. From the 2-microphone design that reduces background noise so you can speak and hear clearly over heavy equipment, diesel engines and sirens to the high-spec RF performance for excellent coverage in challenging environments.

With its easy-to-use interface, color display, intelligent lighting and radio profiles, you get all the power of APX in a compact radio. Plus, you can extend the performance of your radio with a complete portfolio of industry-leading IMPRES smart energy and audio accessories.

COMPACT AND UNCOMPROMISING

A compact P25 Phase 2 capable portable, the APX 2000 gets the job done without getting in the way. With two dedicated knobs for volume and channel control, the APX 2000 provides readiness for any type of work setting. And its standard IP67 and MIL-STD certified to withstand dust, heat, shock, drops and water immersion, so you can count on it wherever you need it – at the factory line, power line or fire line.

P25 PERFORMANCE, INSIDE AND OUT

Loaded with key P25 features to increase safety, the APX 2000 features Mission Critical Wireless, a unique Bluetooth® solution that provides an encrypted link to a high performance earpiece, GPS for quickly locating personnel outdoors, AES encryption for improved security, and over-the-air programming to program radios in the field without interrupting voice operation.

IMPROVE RESPONSE AND EXPENSES

The APX 2000 is P25 Phase 2 capable for twice the voice capacity so you can add more users without adding more frequencies or infrastructure. And it's backwards and forwards compatible with all Motorola mission critical radio systems, so you can interoperate with confidence while you improve operating expenses.

POWER UP WITH APX 2000 ACCESSORIES

- Designed, tested and certified for optimum performance with your radio
- Complete portfolio of remote speaker microphones, headsets and Mission Critical Wireless Bluetooth® accessories
- High-powered IMPRES™ batteries that have a slim design to fit the compact radio size

PRODUCT DATA SHEET
APX™ 2000 P25 PORTABLE RADIO



FEATURES AND BENEFITS

Available in 700/800 MHz, VHF, UHF R1 and UHF R2 bands

Trunking standards supported:

- Clear or digital encrypted ASTRO®25 Trunked Operation
- Capable of SmartZone®, SmartZone Omnilink, SmartNet®

Analog MDC-1200 and Digital APCO P25 Conventional System Configurations

Narrow and wide bandwidth digital receiver (6.25 kHz equivalent / 12.5 kHz / 30 kHz / 25 kHz)¹

Standard with 2 dedicated control knobs for volume and channel changes

Embedded digital signaling (ASTRO & ASTRO 25)

Available in 2 models

Lightbar with Intelligent Lighting

Radio Profiles

Unified Call List

User programmable Voice Announcement

Meets Applicable MIL-STD-810C, D, E, F and G

IP67 standard (submersible 1 meter, 30 minutes)

Instant Recall

Intelligent Priority Scan

Software Key

Superior Audio Features:

- 0.5 W high audio speaker
- 2-mic noise canceling technology

Utilizes Windows 7, 8 and 10 Customer Programming Software (CPS)

- Supports USB communications
- Built in FLASHport™ support

Full portfolio of accessories including IMPRES batteries, chargers and audio devices³

OPTIONAL FEATURES

- AES Encryption
- Programming Over Project 25
- Text Messaging
- Man Down
- Site Selectable Alert Tones
- P25 Over the Air re-keying
- P25 Link Layer Authentication
- Enhanced Data
- Rugged Option: Mil Std 512.X, Delta - T (2 meters for 2 hours)
- Mission Critical Wireless Bluetooth⁴
- ASTRO 25 Integrated Voice & Data
- Integrated GPS/GLONASS for outdoor location tracking
- ANSI/TIA 4950 and CAN/CSA C22.2 NO. 157-92 for Division 1, Class I, Groups C, D; Class II Groups E, F, G; Class III. ANSI/ISA 12.12.01-2015 and CAN/CSA C22.2 No.213-15 Division 2, Class I, Groups A, B, C, D, T3C. Tamb = -25°C to +60°C. Intrinsically Safe when used with Motorola Battery NNTN8560.

¹ Per the FCC Narrowbanding rules, new products (APX2000 VHF, UHF R1, UHF R2) submitted for FCC certification after January 1, 2011 are restricted from being granted certification at 25KHz for United States - State & Local Markets only.

² Radios meet industry standards (IPx7) for immersion.

³ Chargers and batteries for the APX 2000 radios do not interoperate with other APX radios.

⁴ Compatible with BT 2.0 and HSP and PAN BT Profiles.

⁵ When used with a Hazardous Location tested radio.

TRANSMITTER - TYPICAL PERFORMANCE SPECIFICATIONS

	700/800	VHF	UHF Range 1	UHF Range 2
Frequency Range/Bandsplits	700 MHz 800 MHz	763-776, 793-806 MHz 806-825, 851-870 MHz	136-174 MHz	380-470 MHz 450-520 MHz
Channel Spacing		25/12.5 kHz	30/25/12.5 kHz	25/12.5 kHz
Maximum Frequency Separation		Full Bandsplit	Full Bandsplit	Full Bandsplit
Rated RF Output Power Adj ¹		1-3 Watts Max	1-5 Watts Max	1-5 Watts Max
Frequency Stability ¹ (-30°C to +60°C; +25°C Ref.)		±0.00010 %	±0.00010 %	±0.00010 %
Modulation Limiting ¹		±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz
Emissions (Conducted and Radiated) ¹		-75 dB	-75 dB	-75 dB
Audio Response ¹		+1, -3 dB	+1, -3 dB	+1, -3 dB
FM Hum & Noise	25 kHz 12.5 kHz	-47 dB -45 dB	-47 dB -47 dB	-47 dB -45 dB
Audio Distortion ¹	25 kHz 12.5 kHz	1.00%	1.00%	1.00%

BATTERIES FOR APX 2000

Battery Capacity / Type	Dimensions (HxWxD)	Weight	Battery Part Number	Battery Capacity
Li-Ion IMPRES 1900 mAh IP67	114.5x55.04x17.85	150 grams	NNTN8128_	1900 mAh
Li-Ion IMPRES 2300 mAh IP67 Non-HazLoc	114.5x55.04x23.15	160 grams	PMNN4424_	2300 mAh
Li-Ion IMPRES 2300 mAh IP67 HazLoc ⁵	114.5x55.04x23.15	210 grams	NNTN8560_	2500 mAh
Li-Ion IMPRES 2700 mAh IP54 Non-HazLoc	114.5 x 55.04 x 23.15	160 grams	PMNN4448_	2700 mAh



RADIO MODELS		
	MODEL 2	MODEL 3
Display	Full bitmap color LCD display 3 lines of text x 14 characters 1 line of icons 1 menu line x 3 menus White backlight	Full bitmap color LCD display 3 lines of text x 14 characters 1 line of icons 1 menu line x 3 menus White backlight
Keypad	Backlight keypad 3 soft keys 4 direction Navigation key Home and Data buttons	Backlight keypad 3 soft keys 4 direction navigation key 4x3 keypad Home and Data buttons
Channel Capacity	512**	512**
FLASHport Memory	64 MB	64 MB
700/800 MHz (763-870 MHz)	H52UCF9PW6AN	H52UCH9PW7AN
VHF (136-174 MHz)	H52KDF9PW6AN	H52KDH9PW7AN
UHF Range 1 (380-470 MHz)	H52QDF9PW6AN	H52QDH9PW7AN
UHF Range 2 (450-520 MHz)	H52SDF9PW6AN	H52SDH9PW7AN
Buttons & Switches	Large PTT button ■ Angled On/Off Volume Control ■ 16 position top-mounted rotary switch ■ Orange emergency button ■ 3 programmable side buttons	

TRANSMITTER CERTIFICATION

700/800 (764-869 MHz)	AZ489FT7049
VHF (136-174 MHz)	AZ489FT3828
UHF Range 1 (380-470 MHz)	AZ489FT4905
UHF Range 2 (450-520 MHz)	AZ489FT4910

FCC EMISSIONS DESIGNATORS

FCC Emissions Designators	11K0F3E, 16K0F3E, 8K10F1D, 8K10F1E, 8K10F1W, 20K0F1E*
---------------------------	---

POWER SUPPLY

Power Supply	One rechargeable Li-Ion 1900 mAh battery standard with alternate battery options available.
--------------	---

* Per the FCC Narrowbanding rules, new products (APX2000 VHF, UHF1, UHF2) submitted for FCC certification after January 1, 2011 are restricted from being granted certification at 25KHz for United States - State & Local Markets only.
 ** Channel Capacity may be increased from 512 to 1000 when ordered enhanced options.

RECEIVER - TYPICAL PERFORMANCE SPECIFICATIONS

		700/800	VHF	UHF Range 1	UHF Range 2
Frequency Range/Bandsplits	700 MHz 800 MHz	763-776 MHz 851-870 MHz	136-174 MHz	380-470 MHz	450-520 MHz
Channel Spacing		25/12.5 kHz	30/25/12.5 kHz	25/12.5 kHz	25/12.5 kHz
Maximum Frequency Separation		Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit
Audio Output Power at Rated ¹		500mW	500mW	500mW	500mW
Frequency Stability ¹ (-30°C to +60°C; +25°C Ref.)		±0.00010 %	±0.00010 %	±0.00010 %	±0.00010 %
Analog Sensitivity ³	12 dB SINAD	0.250µV	0.216µV	0.234µV	0.234µV
Digital Sensitivity ⁴	1% BER (800 MHz) 5% BER	0.400µV 0.250µV	0.277µV 0.188µV	0.307µV 0.207µV	0.307µV 0.207µV
Selectivity ¹	25 kHz channel 12.5 kHz channel	-76 dB -67 dB	-76 dB -70 dB	-76 dB -67 dB	-76 dB -67 dB
Intermodulation		-75 dB	-79 dB	-77 dB	-77 dB
Spurious Rejection		-76.6 dB	-80.5 dB	-80.3 dB	-80.3 dB
FM Hum and Noise	25 kHz 12.5 kHz	-53 dB -47 dB	-51 dB -45 dB	-50 dB -45 dB	-50 dB -45 dB
Audio Distortion ¹		1.00%	1.00%	1.00%	1.00%

PRODUCT DATA SHEET
APX™ 2000 P25 PORTABLE RADIO

PORTABLE MILITARY STANDARDS 810 C, D, E, F & G											
	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G		
	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II	
High Temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Basic Hot	501.5	I/A1, II/A2	
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I/C3, II/C1	
Temperature Shock	503.1	I	503.2	I/A1C3	503.3	I/A1C3	503.4	I	503.5	I/C	
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I	505.5	I/A1	
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.5	I, III	
Humidity	507.1	II	507.2	II	507.3	II	507.4	1 Proc	507.5	II/Aggravated	
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	1 Proc	509.5	1 Proc	
Blowing Dust	510.1	I	510.2	I	510.3	I	510.4	I	510.5	I	
Blowing Sand	1 Proc	1 Proc	510.2	II	510.3	II	510.4	II	510.5	II	
Vibration	514.2	VIII/F, Curve-W	514.3	I/10, II/3	514.4	I/10, II/3	514.5	I/24	514.6	I/24	
Shock	516.2	I, III, V	516.3	I, V, VI	516.4	I, V, VI	516.5	I, V, VI	516.6	I, V, VI	
Shock (Drop)	516.2	II	516.2	IV	516.4	IV	516.5	IV	516.6	IV	

DIMENSIONS OF THE RADIOS WITHOUT BATTERY				GPS SPECIFICATIONS	
	Inches	Millimeters			
Length	5.42	137.7	Channels		12
Width Push-To-Talk button	2.42	61.4	Tracking Sensitivity		-159 dBm
Depth Push-To-Talk button	1.41	35.75	Accuracy ⁵		<10 meters (95%)
Width Top	2.62	66.55	Cold Start		<60 seconds (95%)
Depth Top	1.84	46.7	Hot Start		<10 seconds (95%)
Weight of the radios without battery	10.05 oz	285 g	Mode of Operation		Autonomous (Non-Assisted) GPS

ENCRYPTION		ENVIRONMENTAL SPECIFICATIONS	
Supported Encryption Algorithms	ADP, AES, (DES-XL, DES-OFB)	Operating Temperature ⁶	-30°C / +60°C
Encryption Algorithm Capacity	8	Storage Temperature ⁶	-40°C / +85°C
Encryption Keys per Radio	Module capable of storing 1024 keys. Programmable for 48 Common Key Reference (CKR) or 16 Physical Identifier (PID)	Humidity	Per MIL-STD
Encryption Frame Re-sync Interval	P25 CAI 300 mSec	ESD	IEC 801-2 KV
Encryption Keying	Key Loader	Water and Dust Intrusion	IP67, Mil Std 512.X, Delta - T
Synchronization	XL – Counter Addressing OFB – Output Feedback		
Vector Generator	National Institute of Standards and Technology (NIST) approved random number generator		
Encryption Type	Digital or Analog		
Key Storage	Tamper protected volatile or non-volatile memory		
Key Erasure	Keyboard command and tamper detection		
Standards	FIPS 140-2 Level 3; FIPS 197		

¹ Measured in the analog mode per TIA / EIA 603 under nominal conditions
² When used with an FM approved intrinsically safe radio
³ Measured conductively in analog mode per TIA / EIA 603 under nominal conditions.
⁴ Measured conductively in digital mode per TIA / EIA IS 102.CAAA under nominal conditions.
⁵ Accuracy specs are for long-term tracking (95th percentile values >5 satellites visible at a nominal -130 dBm signal strength).
⁶ Temperatures listed are for radio specifications. Battery storage is recommended at 25°C, ±5°C to ensure best performance.

Specifications subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements.