

# APX™ 5000 SINGLE-BAND PORTABLE RADIO



From day one, the single-band APX 5000 P25 portable radio has delivered legendary APX ruggedness and reliability, without compromising on the form factor or features required for routine activities and extreme emergencies. Now, as the ever increasing needs of public safety personnel grow, we are evolving the APX 5000 to support newer technologies like WiFi®, Adaptive Audio Engine, and Bluetooth® 4.0 wireless technology. These advances help improve the operational efficiency and response time of public safety agencies while enhancing the safety of personnel and communities.

## VOICE AND DATA, ALL AT ONCE

Update your radio fleet without interrupting voice communications with secure Wi-Fi. This dramatically improves the speed of configuring new codeplugs, firmware and software features over-the-air via Radio Management\*. Agencies can pre-provision up to 20 secure Wi-Fi hotspots so personnel can easily access updates at the facility or in the field.

## HEAR AND BE HEARD

The APX 5000 is equipped with a 3-watt speaker, 3 integrated microphones and the optional Adaptive Audio Engine. This changes the level of noise suppression, microphone gain, windporting and speaker equalization to produce clear and loud audio in any environment.

## SEAMLESS ON-SCENE COMMUNICATION

Ensure fast and seamless communication and collaboration across all responders arriving on a scene. Mission Critical Geofence automatically changes a radio's active talkgroup based on its GPS location and an agency-defined virtual barrier. For example, an incident commander can create a geofence around the 3-block radius of a burning building so that all arriving personnel are automatically placed in the same talkgroup.

## EMERGENCY FIND ME

Bluetooth 4.0 places a wide range of wireless accessories at your disposal and provides personnel with an added level of security by improving response time in emergencies. With Emergency Find Me, a Bluetooth-enabled beacon signal guides other Bluetooth-enabled APX radios within range to assist the user in distress.



\*Radio Management application simplifies APX radio configuration and management by programming up to 16 radios at one time and tracking which radios have been successfully programmed, providing a clear view of the entire radio fleet and a codeplug history for each radio.



## SPECIFICATIONS

### RF BANDS

- 700/800 MHz, VHF, UHF Range 1 & UHF Range 2
- 9600 Baud Digital APCO P25 Phase 1 FDMA and Phase 2 TDMA Trunking
- 3600 Baud SmartNet®, SmartZone®, SmartZone, Omnilink Trunking
- Digital APCO 25, Conventional, Analog MDC 1200, Quick Call II System Configurations Narrow and Wide Bandwidth Digital Receiver (6.25 kHz Equivalent/25/20/12.5 KHz)<sup>1</sup>

### STANDARD FEATURES

- Mission Critical Wireless Bluetooth® 4.0 (LE)<sup>2</sup>
- Emergency Find Me<sup>2</sup>
- ASTRO 25 Integrated Voice & Data
- Integrated GPS/GLONASS for Outdoor Location Tracking
- Voice Announcements
- ISSI 8000 Roaming
- Radio Profiles
- Dynamic Zone
- Intelligent Lighting
- Single-Key ADP Encryption
- IP68 submersion (2 meters, 2 hours)
- IMPRES 2 Battery
- Text Message
- Software Key

### PROGRAMMING

- Utilizes Windows 7, 8 & 10 Customer Programming Software (CPS) with Radio Management<sup>3</sup>

### ADAPTIVE AUDIO ENGINE (OPTIONAL)

- 3 Watt Speaker with Adaptive Equalization
- Adaptive Dual-Sided Operation
- Adaptive Noise Suppression Intensity
- Adaptive Gain Control
- Adaptive Windporting

### OPTIONAL FEATURES

- Wi-Fi® 802.11 b/g/n
- LEX L10 Collaboration
- RFID Volume Knob
- Multi-key for 128 keys and Multi-Algorithm
- Programming Over Project 25 (OTAP)
- Over the Air Rekey (OTAR)
- Digital Tone Signaling
- Mission Critical Geofence
- P25 Authentication
- Man Down Capability
- High Impact Green and Public Safety Yellow Colored Housing Options
- Rugged Option: IP68 (2m/4hr), Mil Std 512.X Delta - T<sup>4</sup>
- ANSI/TIA 4950-A and CAN/CSA C22.2 NO. 157-92 for DIV1, Class I, GRP C, D ANSI/ISA 12.12.01-2015 and CAN/CSA C22.2 No 213-15 For Class II, GRP E, F, G; Class III, DIV2, Class I, GRP A, B, C, D, T3C. Temp = -25C to +60C. Intrinsically Safe when used with NNTN8930A, NNTN8921A

1. Per the FCC Narrowbanding rules, new products (APX 5000 UHF R1, UHF R2 ) submitted for FCC certification after January 1, 2011 are restricted from being granted certification at 25KHz for United States - State & Local Markets only.

2. Compatible with BT 2.1, HSP, PAN, DUN and SPP Profiles found in off-the-shelf BT accessories and BT 4.x

3. Requires CPS version R12.00.00 and greater.

4. Radios meet industry standards (IPx7) for submersion.

## TRANSMITTER - TYPICAL PERFORMANCE SPECIFICATIONS

	700/800	VHF	UHF Range 1	UHF Range 2
Frequency Range/Bandsplits	700 MHz 800 MHz	763-776, 793-806 MHz 806-824, 851-870 MHz	136-174 MHz	380-470 MHz 450-520 MHz
Channel Spacing		25/20/12.5 kHz	25/20/12.5 kHz	25/20/12.5 kHz
Maximum Frequency Separation		Full Bandsplit	Full Bandsplit	Full Bandsplit
Rated RF Output Power Adj <sup>1</sup>		1-3 Watts Max	1-6 Watts Max	1-5 Watts
Frequency Stability <sup>1</sup> (-30°C to +60°C; +25°C Ref.)		±0.00010 %	±0.00010 %	±0.00010 %
Modulation Limiting <sup>1</sup>		±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz
Emissions (Conducted and Radiated) <sup>1</sup>		-75 dB	-75 dB	-75 dB
Audio Response <sup>1</sup>		+1, -3 dB	+1, -3 dB	+1, -3 dB
FM Hum & Noise	25 kHz 12.5 kHz	-52 dB -47 dB	-55 dB -50 dB	-52 dB -46 dB
Audio Distortion <sup>1</sup>		1.00 %	1.00 %	1.00 %

1. Measured in the analog mode per TIA / EIA 603 under nominal conditions

## BATTERIES FOR APX 5000

Battery Capacity / Type	Dimensions (HxWxD)	Weight	Battery Part Number	Battery Capacity
Li-Ion IMPRES 2 2550 mAh <sup>1</sup>	3.4" x 2.3" x 1.5"	5.0 oz	PMNN4485	2550 mAh
Li-Ion IMPRES 2 3400 mAh	3.4" x 2.3" x 1.7"	6.5 oz	PMNN4486	3400 mAh
Li-Ion IMPRES 2 4850 mAh	5" x 2.3" x 1.7"	11.0 oz	PMNN4487	4850 mAh
Li-Ion IMPRES 2 5100 mAh	5" x 2.3" x 1.7"	11.0 oz	PMNN4494	5100 mAh
Li-Ion IMPRES 2 2650 mAh <sup>2</sup>	3.4" x 2.3" x 1.7"	5.7 oz	NNTN8930	2650 mAh
Li-Ion IMPRES 2 4500 mAh <sup>2</sup>	5" x 2.3" x 1.7"	11.0 oz	NNTN8921	4500 mAh

1.The standard shipping battery for the APX5000

2.HAZLOC approved.

## RADIO MODELS

MODEL 1.5



MODEL 2.5



MODEL 3.5



Display	Full bitmap monochromatic LCD top display 1 line text x 8 characters 1 line of icons No menu support Multi-color backlight	Top display plus: Full bitmap color LCD display 4 lines of text x 14 characters 2 lines of icons 1 menu line x 3 menus White backlight	Top display plus: Full bitmap color LCD display 4 lines of text x 14 characters 2 lines of icons 1 menu line x 3 menus White backlight
Keypad	none	Backlight keypad 3 soft keys 4 direction Navigation key Home and Data buttons	Backlight keypad 3 soft keys 4 direction navigation key 4x3 keypad Home and Data buttons
Channel Capacity <sup>1</sup>	96	1000	1000
FLASHport Memory	64 MB	64 MB	64 MB
700/800 MHz (763-870 MHz)	H98UCD9PW5BNI	H98UCF9PW6BNI	H98UCH9PW7BNI
VHF (136-174 MHz)	H98KGD9PW5BNI	H98KGF9PW6BNI	H98KGH9PW7BNI
UHF Range 1 (380-470 MHz)	H98QDD9PW5BNI	H98QDF9PW6BNI	H98QDH9PW7BNI
UHF Range 2 (450-520 MHz)	H98SDD9PW5BNI	H98SDF9PW6BNI	H98SDH9PW7BNI

### Buttons & Switches

Large PTT button ■ Angled On/Off volume control ■ Orange emergency button ■ 16 position top-mounted rotary switch  
■ 2-position concentric switch ■ Multi-color backlight ■ 3-position toggle switch ■ 3 programmable side buttons

### Regulatory Information

	FCC ID	Industry Canada
700/800 (764-869 MHz)	AZ489FT7086 <sup>1</sup>	109U-89FT7086
VHF (136-174 MHz)	AZ489FT7087 <sup>1</sup>	109U-89FT7087
UHF Range 1 (380-470 MHz)	AZ489FT7077 <sup>1</sup>	109U-89FT7077
UHF Range 2 (420-520 MHz)	AZ489FT7085 <sup>1</sup>	109U-89FT7085

### FCC Emissions Designators

FCC Emissions Designators 11K0F3E, 16K0F3E, 8K10F1D, 8K10F1E, 8K10F1W, 20K0F1E

### Power Supply

Power Supply One rechargeable 2550 mAh Li-Ion Battery Standard (PMNN4485), with alternate battery options available.

1.Enhancement package available

## RECEIVER - TYPICAL PERFORMANCE SPECIFICATIONS

		700/800	VHF	UHF Range 1	UHF Range 2
Frequency Range/Bandsplits	700 MHz 800 MHz	763-776 MHz 851-870 MHz	136-174 MHz	380-470 MHz	450-520 MHz
Channel Spacing		25/20/12.5 kHz	25/20/12.5 kHz	25/20/12.5 kHz	25/20/12.5 kHz
Maximum Frequency Separation		Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit
Audio Output Power at Rated <sup>1</sup>		500 mW	500 mW	500 mW	500 mW
Analog Sensitivity <sup>2</sup>	12 dB SINAD	0.25 $\mu$ V	0.17 $\mu$ V	0.224 $\mu$ V	0.203 $\mu$ V
Digital Sensitivity <sup>3</sup>	1% BER (800 MHz) 5% BER	0.375 $\mu$ V 0.24 $\mu$ V	0.243 $\mu$ V 0.15 $\mu$ V	0.298 $\mu$ V 0.200 $\mu$ V	0.296 $\mu$ V 0.204 $\mu$ V
Selectivity <sup>1</sup>	25 kHz channel 12.5 kHz channel	-76 dB -70 dB	-78 dB -73 dB	-77 dB -67 dB	-76 dB -67 dB
Intermodulation		-80.1 dB	-80.2 dB	-80.3 dB	-80.2 dB
Spurious Rejection		-75 dB	-78 dB	-80.5 dB	-80.8 dB
FM Hum and Noise	25 kHz 12.5 kHz	-54 dB -49 dB	-54.3 dB -50.1 dB	-53.5 dB -47.5 dB	-52.5 dB -47.3 dB
Audio Distortion at Rated <sup>1</sup>		0.90 %	0.90 %	0.70 %	0.70 %

1. Measured in the analog mode per TIA / EIA 603 under nominal conditions.

2. Measured conductively in analog mode per TIA / EIA 603 under nominal conditions.

3. Measured conductively in digital mode per TIA / EIA IS 102.CAAA under nominal conditions.





**PORTABLE MILITARY STANDARDS 810 C, D, E, F & G**

	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G	
	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
High Temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Basic Hot	501.5	I/A1, II/A2
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I/C3, II/C1
Temperature Shock	503.1	I	503.2	I/A1C3	503.3	I/A1C3	503.4	I	503.5	I/C
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I	505.5	I/A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.5	I, III
Humidity	507.1	II	507.2	II	507.3	II	507.4	1 Proc	507.5	II/Aggravated
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	1 Proc	509.5	1 Proc
Blowing Dust	510.1	I	510.2	I	510.3	I	510.4	I	510.5	I
Blowing Sand	1 Proc	1 Proc	510.2	II	510.3	II	510.4	II	510.5	II
Immersion	512.1	I	512.2	I	512.3	I	512.4	I	512.5	I
Vibration	514.2	VIII/F, Curve-W	514.3	I/10, II/3	514.4	I/10, II/3	514.5	I/24	514.6	I/24
Shock	516.2	I, III, V	516.3	I, V, VI	516.4	I, V, VI	516.5	I, V, VI	516.6	I, V, VI
Shock (Drop)	516.2	II	516.2	IV	516.4	IV	516.5	IV	516.6	IV



## DIMENSIONS OF THE RADIOS WITHOUT BATTERY

	Inches	Millimeters
Length	5.47	139
Width Push-To-Talk button	2.39	60.7
Depth Push-To-Talk button	1.40	35.6
Width Top	2.98	75.7
Depth Top	1.58	40.1
Depth Bottom of Battery	1.24	31.5
Weight of the radios without battery	10.9 oz	309 g

## ENCRYPTION

Supported Encryption Algorithms	ADP, AES, DES, DES-XL, DES-OFB, DVP-XL
Encryption Algorithm Capacity	8
Encryption Keys per Radio	Module capable of storing 1024 keys. Programmable for 64 Common Key Reference (CKR) or 16 Physical Identifier (PID)
Encryption Frame Re-sync Interval	P25 CAI 300 mSec
Encryption Keying	Key Loader
Synchronization	XL – Counter Addressing OFB – Output Feedback
Vector Generator	National Institute of Standards and Technology (NIST) approved random number generator
Encryption Type	Digital
Key Storage	Tamper protected volatile or non-volatile memory
Key Erasure	Keyboard command and tamper detection
Standards	FIPS 140-2 Level 3 FIPS 197

## GPS/GPS/GNSS SPECIFICATIONS

Constellations	GPS & GLONASS
Tracking Sensitivity	-164 dBm
Accuracy <sup>2</sup>	<5 meters (95%)
Cold Start	<60 seconds (95%)
Hot Start	<5 seconds (95%)
Mode of Operation	Autonomous (Non-Assisted)

## RUGGED SPECIFICATIONS

Leakage (submersion)	MIL-STD-810 C, D, E, F and G Method 512.X Procedure I, IP68 (2 meters, 4 hours)
----------------------	---------------------------------------------------------------------------------------

## HOUSING COLOR

Black (Standard), Public Safety Yellow, and High Impact Green

## ENVIRONMENTAL SPECIFICATIONS

Operating Temperature <sup>1</sup>	-30°C / +60°C
Storage Temperature <sup>1</sup>	-50°C / +85°C
Humidity Per MIL-STD	ESD IEC 801-2 KV
Water and Dust Intrusion	IP68 (2 meters, 4 hours)

1. Temperatures listed are for radio specifications. Battery storage is recommended at 25°C, ±5°C to ensure best performance.

2. Measured conductively with >6 satellites visible at a nominal -130 dBm signal strength. Specs provided are 95th percentile values.

## EMISSION DESIGNATORS

LMR: 8K10F1D, 8K10F1E, 8K10F1V, 11K0F3E, 16K0F3E, 20K0F1E

Bluetooth®: 852KF1D, 1M17F1D, 1M19F1D, 1M04F1D

WLAN (Wi-Fi): 13M7G1D, 17M0D1D, 18M1D1D

## WIRELESS CONNECTIVITY AND SECURITY

Frequency Range/Bandsplits:

Bluetooth: 2402 - 2480 MHz, WLAN (Wi-Fi): 2400 - 2483.5 MHz

WLAN (Wi-Fi) 802.11 b/g/n supports WPA-2, WPA, WEP security protocols; radio can be pre-provisioned with up to 20 SSIDs<sup>1</sup>

Mission Critical Wireless Bluetooth 2.1 uses 96 bit encryption for pairing & 128 bit encryption for voice, signaling and data. The radio BT supports up to 6 data connections and 1 audio connection

Bluetooth 4.0 Low Energy uses 128-bit AES-CCM encryption

<sup>1</sup>1.2400 - 2483.5 MHz for EMEA region and includes guardband.  
Channels 1 – 11 used for FCC/IC region.



For more information, please visit [www.motorolasolutions.com/apx](http://www.motorolasolutions.com/apx)

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2018 Motorola Solutions, Inc. All rights reserved. 02-2018

