



# APX™ 7000XE PROJECT 25 MULTIBAND PORTABLE RADIO

We take the safety of first responders personally, which is why we designed the APX™ 7000XE – the most advanced, ultra-rugged radio with innovative features designed by first responders for first responders working in extreme environments.

Together we have created an ergonomically-superior radio that is easy to operate, with glove-friendly controls and a large top display. Significantly louder and clearer so that every word is heard when you're battling noise in almost any environment. A mission critical multiband, multi-protocol radio so seamless, you can be confident your communications are truly interoperable.

Focus on the task, not the technology, with the high-performing portable that stands up and stands out in the toughest conditions.

## ADVANCED ERGONOMICS FOR EXTREME CONDITIONS

- Easy to grip, hold and control in harsh conditions
- Glove-friendly controls are big, recognizable and easy to distinguish
- Well-spaced knobs eliminate accidental activation
- Enlarged top display is easy to read, in dark or low light
- Shielded push-to-talk button is easy to use with a gloved hand
- Largest emergency button in the industry

## EXCEPTIONAL AUDIO MEANS EVERY WORD IS HEARD

- 50% louder and clearer without distorting transmissions
- Dual microphone locates the talker, cancels out ambient noise
- Extreme Audio Profile reduces background noise and improves voice clarity
- Equipped with the latest AMBE digital voice vocoder
- New speaker grill design for improved water runoff

## NEXT GENERATION TECHNOLOGY TO RELY ON NOW

- Project 25 Phase 2 technology provides twice the voice capacity
- Multiband operation ensures seamless interoperability
- Backwards and forwards compatible with all Motorola mission critical radio systems
- Future-ready for applications like Mission Critical Wireless and GPS location tracking

- Channel Capacity
  - Top Display - 1,200
  - Dual Display - 2,000
- Universal Push-to-Talk
- T-Grip
- Dual Battery Latch
- Extra large emergency button
- 16 position rotary switch
- 2 position concentric switch
- 3 position toggle switch
- 3 programmable side buttons
- Transmit LED indicator
- Tall Top Display
  - 1 line of icons
  - 1 line x 8 characters of text
- Standard Rugged
- HazLoc



### FEATURES AND BENEFITS:

- Available in 700-800 MHz, VHF, UHF Range 1 and 2 bands
- Optional multiband operation
- Trunking standards supported:
  - Clear or digital encrypted ASTRO®25 Trunked Operation
  - Capable of SmartZone®, SmartZone Omnilink, SmartNet®
- Analog MDC-1200 and Digital APCO P25 Conventional System Configurations
- Narrow and wide bandwidth digital receiver\*
- 6.25 kHz equivalent/12.5 kHz/30 kHz/25 kHz
- Embedded digital signaling (ASTRO & ASTRO 25)
- Seamless wideband scan
- ASTRO 25 Integrated Voice & Data
- Integrated GPS/GLONASS for outdoor location tracking
- Intelligent Priority Scan
- Software Key
- Intelligent Lighting
- Radio Profiles
- Expansion Slot
- Micro SD removable memory card
- User programmable voice announcement
- Instant Recall

- Meets Applicable MIL-STD-810C, D, E, F and G
- Select frequency band combinations
- Ships standard HAZ LOC approved and Rugged\*\*
- Yellow and green colored housing options

### Superior Audio Features:

- Extreme Audio Profile
- 1W high audio speaker
- Dual speakers (Model 3.5 only)
- Dual sided 2 microphone noise canceling technology

Utilizes Windows XP, Vista and Windows 7 and 8 Customer Programming Software (CPS)\*\*\*\*

- Supports USB communications
- Built in FLASHport™ support

Full portfolio of accessories including the XE Remote Speaker Microphone specifically designed for performance in extreme environments.

Mission Critical Wireless Bluetooth\*\*\*

### OPTIONAL FEATURES:

- Enhanced Encryption capability
- Programming Over Project 25
- Over the Air Rekey
- Text Messaging
- Man Down

\*Per the FCC Narrowbanding rules, new products (APX 7000XE UHF R1 - UHF R2 combination) submitted for FCC certification after January 1st, 2011 are restricted from being granted certification at 25 kHz for United States - State & Local Markets only. All other band combinations will comply with FCC Narrowbanding rules January 1st, 2013.

\*\* Rugged radios exceed industry standards (IPX7) for submersion and provide a higher level of water protection—MIL-STD-810E, Method 512.3 Immersion. These radios meet the incremental requirement of submersion in 1 meter of fresh water that is 27C colder than the product.

HAZ LOC Certification & Level is dependent on configuration ordered.

\*\*\* Compatible with BT 2.1 HSP, PAN, DUN and SPP Profiles

\*\*\*\* CPS version R12.00.00 and greater ordered after June 2014 will only support Windows 7 and 8

## TRANSMITTER - TYPICAL PERFORMANCE SPECIFICATIONS

	700 MHz	800 MHz	VHF	UHF Range 1	UHF Range 2
Frequency Range/Bandsplits	763-776 MHz 793-806 MHz	806-824 MHz 851-870 MHz	136-174 MHz	380-470 MHz	450-520 MHz
Channel Spacing	25/12.5 kHz	25/12.5 kHz	30/25/12.5 kHz	25/20/12.5 kHz	25/12.5 kHz
Maximum Frequency Separation	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit
Rated RF Output Power Adj <sup>1</sup>	1-2.5 Watts	1-3 Watts	1-6 Watts	1-5 Watts	1-5 Watts
Frequency Stability <sup>1</sup> (-30°C to +60°C; +25°C Ref.)	±0.00010%	±0.00010%	±0.00010%	±0.00010%	±0.00010%
Modulation Limiting <sup>1</sup>	±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz
Emissions (Conducted and Radiated) <sup>1</sup>	-75 dB	-75 dB	-75 dB	-75 dB	-75 dB
Audio Response <sup>1</sup>	+1, -3 dB	+1, -3 dB	+1, -3 dB	+1, -3 dB	+1, -3 dB
FM Hum & Noise	25 kHz 12.5 kHz	-48 dB -46 dB	-47 dB -45 dB	-47 dB -45 dB	-47 dB -45 dB
Audio Distortion <sup>1</sup>	0.60 %	1 %	0.50 %	0.50 %	0.50 %

## BATTERIES FOR APX 7000XE

Battery Capacity / Type	Dimensions (HxWxD)	Weight	Battery Part Number	Battery Capacity
Li-Ion IMPRES 2, 2300 mAh, TIA 4950-A, IP68**†	3.4" x 2.3" x 1.7"	6.5 oz	NNTN8930	2300 mAh
Li-Ion IMPRES 2, 3400 mAh	3.4" x 2.3" x 1.7"	6.5 oz	PMNN4486	3400 mAh
Li-Ion IMPRES 2, 4500 mAh, TIA 4950-A, IP68†	5.0" x 2.3" x 1.7"	11.3 oz	NNTN8921	4500 mAh
Li-Ion IMPRES 2, 4850 mAh	5.0" x 2.3" x 1.7"	11.0 oz	PMNN4487	4850 mAh
Li-Ion IMPRES 2, 5100 mAh	5.0" x 2.3" x 1.7"	11.0 oz	PMNN4494	5100 mAh
Li-Ion IMPRES 2, 3100 mAh, TIA 4950-A, IP68	3.4" x 2.3" x 1.7"	7.1 oz	PMNN4547	3100 mAh

\* Standard shipping battery

† HazLoc approval only available on 7/800 MHz and VHF band combinations

## RECEIVER - TYPICAL PERFORMANCE SPECIFICATIONS

		700 MHz	800 MHz	VHF	UHF Range 1	UHF Range 2
Frequency Range/Bandsplits		763-776 MHz	851-870 MHz	136-174 MHz	380-470 MHz	450-520 MHz
Channel Spacing		25/12.5 kHz	25/12.5 kHz	30/25/12.5 kHz	25/12.5 kHz	25/12.5 kHz
Maximum Frequency Separation		Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit
Audio Output Power at Rated <sup>1</sup>		1000 mW	1000 mW	1000 mW	1000 mW	1000 mW
Frequency Stability <sup>1</sup> (-30°C to +60°C; +25°C Ref.)		±0.00010 %	±0.00010 %	±0.00010 %	±0.00010 %	±0.00010 %
Analog Sensitivity <sup>2</sup>	12 dB SINAD	0.250 µV	0.250 µV	0.216 µV	0.234 µV	0.234 µV
Digital Sensitivity <sup>2</sup>	1% BER	0.347 µV	0.333 µV	0.277 µV	0.307 µV	0.307 µV
	5% BER	0.251 µV	0.251 µV	0.188 µV	0.207 µV	0.207 µV
Selectivity <sup>1</sup>	25 kHz channel	75.7 dB	75.7 dB	79.3 dB	78.3 dB	78.3 dB
	12.5 kHz channel	67.5 dB	67.5 dB	70 dB	68.1 dB	67.5 dB
Intermodulation Rejection		80 dB	80 dB	80.5 dB	80.2 dB	80.2 dB
Spurious Rejection		76.6 dB	76.6 dB	93.2 dB	80.3 dB	80.3 dB
FM Hum & Noise	25 kHz	-54 dB	-54 dB	-53.8 dB	-53.5 dB	-53.5 dB
	12.5 kHz	-48 dB	-48 dB	-48 dB	-47.4 dB	-47.4 dB
Audio Distortion <sup>1</sup>		0.9 %	0.9 %	1.20 %	0.91 %	0.91 %

## RADIO MODELS

### Model 1.5 Top Display

Display	Tall monochromatic LCD top display ■ 1 line text, 8 characters ■ 1 line of icons ■ No menu support ■ Multi-color backlight	
Keypad	None	
Channel Capacity	1200	
FLASHport Memory	64 MB	
700/800 MHz (763-870 MHz)	Model H49TGD9PW1AN, Primary QA00569, Secondary QA00573	
VHF (136-174 MHz)	Model H49TGD9PW1AN, Primary QA00570, Secondary QA00574	
UHF Range 1 (380-470 MHz)	Model H49TGD9PW1AN, Primary QA00571, Secondary QA00575	
UHF Range 2 (450-520 MHz)	Model H49TGD9PW1AN, Primary QA00572, Secondary QA00576	
Buttons & Switches	Large PTT button ■ Angled on/off volume knob ■ X-large emergency button ■ 16 position top mounted rotary knob ■ 2-position concentric switch ■ 3-position toggle switch ■ 3 programmable side buttons	
Embedded	GPS LED	Yes Multi-color

### Model 3.5 Dual Display

Display	Tall monochromatic LDC top display ■ Large color LCD front display ■ 4 lines text, 14 characters ■ 2 lines of icons ■ 1 menu line, 3 menus, White backlight	
Keypad	Backlight Keypad ■ 3 soft keys ■ 4-direction navigation key ■ 4x3 keypad ■ Home and Data buttons	
Channel Capacity	3000	
FLASHport Memory	64 MB	
700/800 MHz (764-870 MHz)	Model H49TGD9PW1AN, Primary QA00569, Secondary QA00573, Keypad/Dual Display QA00577	
VHF (136-174 MHz)	Model H49TGD9PW1AN, Primary QA00570, Secondary QA00574, Keypad/Dual Display QA00577	
UHF Range 1 (380-470 MHz)	Model H49TGD9PW1AN, Primary QA00571, Secondary QA00575, Keypad/Dual Display QA00577	
UHF Range 2 (450-520 MHz)	Model H49TGD9PW1AN, Primary QA00572, Secondary QA00576, Keypad/Dual Display QA00577	
Buttons & Switches	Large PTT button ■ Angled On/Off Volume knob ■ Extra large emergency button ■ 16 position top mounted rotary knob ■ 2-position concentric switch ■ 3-position toggle switch ■ 3 programmable side buttons ■ Multi-color backlight	
Embedded	GPS LED	Yes Multi-color

### Transmitter Certification - per FCC Grant of Equipment Authorization

VHF – 700/800 MHz	AZ489FT7036 (136-174 MHz and 764-869 MHz)
UHF R1 – 700/800 MHz	AZ489FT7040 (380-470 MHz and 764-869 MHz)
UHF R1 – VHF	AZ489FT4886 (380-470 MHz and 136-174 MHz)
UHF R2 – 700/800 MHz	AZ489FT7042 (450-520 MHz and 764-869 MHz)
UHF R2 – VHF	AZ489FT4893 (450-520 MHz and 136-174 MHz)
Bluetooth	AZ489FT6000 (2402-2480 MHz)

### FCC Emission Designators

FCC Emission Designators	11K0F3E, 16K0F3E, 8K10F1D, 8K10F1E, 8K10F1W, 20K0F1E*
--------------------------	---

### Power Supply

Power Supply	One rechargeable 2650 mAh TIA 4950-A Li-Ion Standard Battery (NNTN8930) available for 7/800 MHz & VHF band combinations.
--------------	--

## PORTABLE MILITARY STANDARDS 810 C, D, E, F & G

	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G	
	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
High Temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Basic Hot	501.5	I/A1, II/A2
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I/C3, II/C1
Temperature Shock	503.1	I	503.2	I/A1C3	503.3	I/A1C3	503.4	I	503.5	I/C
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I	505.5	I/A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.5	I, III
Humidity	507.1	II	507.2	II	507.3	II	507.4	1 Proc	507.5	II/Aggravated
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	1 Proc	509.5	1 Proc
Blowing Dust	510.1	I	510.2	I	510.3	I	510.4	I	510.5	I
Blowing Sand	1 Proc	1 Proc	510.2	II	510.3	II	510.4	II	510.5	II
Submersion (Delta-T)	512.1	I	512.2	I	512.3	I	512.4	I	512.5	I
Vibration	514.2	VIII/F, Curve-W	514.3	I/10, II/3	514.4	I/10, II/3	514.5	I/24	514.6	I/24
Shock	516.2	I, III, V	516.3	I, V, VI	516.4	I, V, VI	516.5	I, V, VI	516.6	I, V, VI
Shock (Drop)	516.2	II	516.2	IV	516.4	IV	516.5	IV	516.6	IV

### ENCRYPTION

Supported Encryption Algorithms	ADP, AES, DES, DES-XL, DES-OFB, DVP-XL
Encryption Algorithm Capacity	8
Encryption Keys per Radio	Module capable of storing 1024 keys. Programmable for 128 Common Key Reference (CKR) or 16 Physical Identifier (PID)
Encryption Frame Re-sync Interval	P25 CAI 300 mSec
Encryption Keying	Key Loader
Synchronization	XL – Counter Addressing OFB – Output Feedback
Vector Generator	National Institute of Standards and Technology (NIST) approved random number generator
Encryption Type	Digital
Key Storage	Tamper protected volatile or non-volatile memory
Key Erasure	Keyboard command and tamper detection
Standards	FIPS 140-2 Level 3 FIPS 197

### RUGGED OPTION SPECIFICATIONS

Leakage (submersion)	MIL-STD-810 C,D,E,F and G Method 512.X Procedure I
Housing Availability	Black (Standard), Public Safety Yellow and High Impact Green
Hazardous Location/ Intrinsic Safety (IS) <sup>5</sup>	Class I, Division 1, Group D; Class II, Division 1, Group E, F, G; Class III, Hazardous (Classified) Locations

### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-30°C / +60°C
Storage Temperature	-40°C / +85°C
Humidity	MIL-STD 507.x PROC. II
ESD	IEC 801-2 KV
Water and Dust Intrusion	Mil Std 512.X, Delta - T

### GPS SPECIFICATIONS

Channels	12
Tracking Sensitivity	-151 dBm
Accuracy <sup>4</sup>	<10 meters (95%)
Cold Start	<60 seconds (95%)
Hot Start	<10 seconds (95%)
Mode of Operation	Autonomous (Non-Assisted) GPS

### DIMENSIONS OF THE RADIOS WITHOUT BATTERY

	Inches	Millimeters
Height	6.94	176.3
Width Push-To-Talk button	2.39	60.8
Depth Push-To-Talk button	1.40	35.6
Width Top	3.32	84.3
Depth Top	2.18	55.4
Depth Bottom	1.25	31.7
Weight of the radios without battery	15.4 oz	439 g

<sup>1</sup> Measured in the analog mode per TIA / EIA 603 under nominal conditions

<sup>2</sup> Measured conductively in digital mode per TIA / EIA IS 102.CAAA under nominal conditions

<sup>3</sup> Accuracy specs are for long-term tracking (95th percentile values >5 satellites visible at a nominal -130 dBm signal strength)

<sup>4</sup> Temperatures listed are for radio specifications. Battery storage is recommended at 25°C, ±5°C to ensure best performance

<sup>5</sup> Only when ordered with IS battery. Only available on 7/800 MHz & VHF band combinations.

Specifications subject to change without notice. All specifications shown are typical.

Radio meets applicable regulatory requirements.

Motorola Solutions, Inc. 1301 East Algonquin Road Schaumburg, Illinois 60196, U.S.A. 800-367-2346  
[motorolasolutions.com](http://motorolasolutions.com)

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2016 Motorola Solutions, Inc. All rights reserved. 06-2016

