

APX™ 8000HXE

ALL-BAND P25 HAZLOC PORTABLE RADIO

APX 8000 SERIES

360 DEGREES OF SAFETY.

AS FIREFIGHTERS, YOU ROUTINELY PUT YOURSELVES IN HARM'S WAY. YOU SHOULDN'T NEED TO WORRY THAT THE EQUIPMENT YOU CARRY IS UP TO THE TASK.

As our flagship radio for fire and rescue, the APX 8000HXE is designed for the most hazardous conditions. Because the APX 8000HXE is certified to Div 1 HazLoc standards, you can be confident entering areas where unknown chemicals and gases add to an already dangerous situation.

Breaking communication barriers, all-band technology connects you with other agencies and departments, no matter which frequency they're on. And when you need to relay a message in a cacophony of alarms and sirens, the Adaptive Audio Engine dynamically adjusts the radio's audio response for optimal clarity, every time.

We collaborated closely with fire and rescue workers to develop the APX 8000HXE, and that's why it's ready for anything - submersion in deep water, impacts that would destroy a typical radio. With exaggerated controls for gloved-hand use, a pressure-tested tempered glass display and a shock-absorbing aluminum alloy endoskeleton, the APX 8000HXE delivers instant communication with total reliability.

Because every second matters when you're saving lives.

-  RESPOND WITH CONFIDENCE
-  ALL BANDS, NO BOUNDARIES
-  PURPOSE-BUILT. MISSION-READY.
-  SOUND MATTERS
-  CONQUER CHAOS
-  ALL THE SUPPORT YOU NEED



**RESPOND WITH
CONFIDENCE**

Certified to Div1 HazLoc standards, the APX 8000HXE is safe to use in areas where there are high concentrations of flammable gas, vapor, liquid, or dust.

**ALL BANDS,
NO BOUNDARIES**

The APX 8000HXE transmits and receives on all commonly used frequencies, so your fire and rescue workers can communicate with different agencies using the same radio.

**SOUND
MATTERS**

Make sure you can hear - and be heard. The APX 8000HXE adaptive audio engine gives you the loudest, clearest audio at any volume, in any environment.

**CONQUER
CHAOS**

With a water-tight seal, drop-resistant dual battery latch, pressure-tested tempered glass display and a shock-absorbing aluminum alloy endoskeleton, the APX 8000HXE is built to survive everything from falls to floods.

**PURPOSE-BUILT.
MISSION-READY.**

Communicate instantly when lives are on the line. With an intuitive design and exaggerated controls, the APX 8000HXE is purpose-built for fire and rescue workers.

**ALL THE SUPPORT
YOU NEED**

Motorola Solutions offers three levels of service plans—Premier, Advanced, and Essential—so you can manage in the way that suits you best.



FEATURES

OPERATION MODES
Digital Trunking: 9600 Baud APCO P25 Phase 1 FDMA and Phase 2 TDMA
Analog Trunking: 3600 Baud SmartNet®, SmartZone®, Omnilink
Digital Conventional: APCO 25
Analog Trunking: MDC 1200, Quik-Call II
ASTRO 25 Integrated Voice & Data (optional)

MODELS AVAILABLE
All-band: VHF, UHF (ranges 1 and 2), 700 and 800 MHz, Model 2.5 and 3.5

CONNECTIVITY
Mission-Critical Bluetooth (version 4.0)
Wi-Fi (802.11b/g/n) ¹
Data Modem Collaboration over Wi-Fi ¹

AUDIO FEATURES
3 W Speaker with Adaptive Equalization
Adaptive Dual-sided Operation
Adaptive Noise Suppression Intensity
Adaptive Gain Control
Adaptive Windporting
Compatible with IMPRES 2 Audio Accessories ²

MANAGEMENT
Customer Programming Software (CPS), version R12.00.00 or later
Radio Management
Over-the-air Programming (OTAP) ¹

SAFETY
Location-Tracking (GPS and GLONASS)
Mission-critical Geofence ¹
Man Down ¹

DIMENSIONS

RADIO WITHOUT BATTERY		
Height (radio body)	6.7 in	169.7 mm
Width	3.3 in	84 mm
Depth	2.2 in	56 mm
Weight	15.6 oz	442 g

RADIO WITH STANDARD BATTERY		
Height (radio body)	6.9 in	176.5 mm
Width	3.3 in	84 mm
Depth	2.2 in	56 mm
Weight	22.7 oz	643 g

HAZLOC (UL/CSA)
Class I, Div 1, Groups C*, D; Class I, Div 2, Groups A, B, C, D; Class II, Div 1, Group E, F, G; Class III; T3C. ³

^{*} Groups C only applies to UL.

SECURITY
Single-key ADP Encryption
Software Key
P25 Authentication ¹
Multikey for 128 keys and multi-algorithm ¹
Over-the-air Rekeying (OTAR) ¹

INGRESS PROTECTION
MIL-STD Delta-T, IP68 submersion (2 m, 4 hr) (Standard)

OTHER FEATURES
Text Messaging
Voice Announcements
Radio Profiles
Dynamic Zone
Intelligent Lighting
IMPRES 2 Battery
RFID Volume Knob ¹
Digital Tone Signaling ¹
Instant Recall
Intelligent Priority Scan



Weight with standard battery
22.7 oz (643 g)

¹ Optional.
² Review accessory catalog and UL manual for more details.
³ Review UL manual for more details.



RADIO MODELS		
	MODEL 3.5	MODEL 2.5
Display	Full bitmap color LCD front display <ul style="list-style-type: none">• 2 lines of status icons• 4 lines of text x 14 characters• 1 line of menu x 3 keys• White backlight	Full bitmap color LCD front display <ul style="list-style-type: none">• 2 lines of status icons• 4 lines of text x 14 characters• 1 line of menu x 3 keys• White backlight
	Full bitmap mono LCD top display <ul style="list-style-type: none">• 1 line of text x 8 characters• 1 line of status icons• Multi-color backlight	Full bitmap mono LCD top display <ul style="list-style-type: none">• 1 line of text x 8 characters• 1 line of status icons• Multi-color backlight
Keypad	4x3 keypad	-
	3 soft keys	3 soft keys
	4-way navigation pad	4-way navigation pad
	Home key	Home key
	Data key	Data key
Channel Capacity	3000	3000
FLASHport Memory	2 GB	2 GB
Part Number	H91TGD9PW9AN	H91TGD9PW8AN
Buttons and Switches	Non-slip PTT button	Non-slip PTT button
	Emergency button (orange)	Emergency button (orange)
	Power / volume knob (angled)	Power / volume knob (angled)
	Rotary selector, 16-position	Rotary selector, 16-position
	Concentric switch, 2-position	Concentric switch, 2-position
	A/B/C switch, 3-position	A/B/C switch, 3-position
	3 programmable side buttons	3 programmable side buttons



TRANSMITTER					
	VHF	UHF 1	UHF 2	700MHz	800MHz
Frequency Range / Bandsplits	136-174 MHz	380-470 MHz	450-520 MHz	792-806 MHz	806-825, 851-870 MHz
Channel Spacing ¹	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz
Maximum Frequency Separation	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit
Rated RF Output Power (Adjustable) ²	1-6 W	1-5 W	1-5 W	1-2.5 W	1-3 W
Frequency Stability (-30 °C to +60 °C; +25 °C Ref.) ²	±1.0 ppm	±1.0 ppm	± 1.0 ppm	± 1.0 ppm	± 1.0 ppm
Modulation Limiting (12.5 / 20 / 25 kHz channel) ²	±2.5 / ±4 / ±5 kHz	±2.5 / ±4 / ±5 kHz	±2.5 / ±4 / ±5 kHz	±2.5 / ±4 / ±5 kHz	±2.5 / ±4 / ±5 kHz
Emissions (conducted and radiated) ²	-75 dBc	-75 dBc	-75 dBc	-75 dBc	-75 dBc
Audio Response ²	+1, -3 dB	+1, -3 dB	+1, -3 dB	+1, -3 dB	+1, -3 dB
FM Hum and Noise (12.5 / 25 kHz channel) ²	-51 / -51 dB	-51 / -51 dB	-47 / -51 dB	-47 / -49 dB	-46 / -49 dB
Audio Distortion (12.5 / 25 kHz channel) ²	0.50% / 0.90%	0.50% / 0.90%	0.60% / 0.90%	0.90% / 0.90%	0.90% / 0.60%

RECEIVER					
	VHF	UHF 1	UHF 2	700MHz	800MHz
Frequency Range / Bandsplits	136-174 MHz	380-470 MHz	450-520 MHz	762-776MHz	851-870 MHz
Channel Spacing ¹	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz
Maximum Frequency Separation	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit
Audio Output at Rated ²	3 W	3 W	3 W	3 W	3 W
Audio Output at Max ²	5 W	5 W	5 W	5 W	5 W
Frequency Stability (-30 °C to +60 °C; +25 °C Ref.) ²	±1.0 ppm	±1.0 ppm	±1.0 ppm	±1.0 ppm	±1.0 ppm
Analog Sensitivity (12 dB SINAD) Standard ²	0.168 µV (-122.5 dBm)	0.199 µV (-121.0 dBm)	0.199 µV (-121.0 dBm)	0.224 µV (-120.0 dBm)	0.224 µV (-120.0 dBm)
Digital Sensitivity (1% BER) ³	0.251 µV (-119.0 dBm)	0.282 µV (-118.0 dBm)	0.282 µV (-118.0 dBm)	0.316 µV (-117.0 dBm)	0.316 µV (-117.0 dBm)
Digital Sensitivity (5% BER) ³	0.149 µV (-123.5 dBm)	0.158 µV (-123.0 dBm)	0.158 µV (-123.0 dBm)	0.211 µV (-120.5 dBm)	0.211 µV (-120.5 dBm)
Selectivity (12.5 / 25 kHz channel) ²	-77 / -82 dB	-74 / -80 dB	-74 / -80 dB	-72 / -79 dB	-72 / -78 dB
Intermodulation (12.5 / 25 kHz channel) Standard ²	-82 dB	-80 dB	-80 dB	-81 dB	-80 dB
Spurious Rejection ²	-92 dB	-98 dB	-98 dB	-98 dB	-98 dB
FM Hum and Noise (12.5 / 25 kHz channel) ²	-55 / -57 dB	-54 / -56 dB	-54 / -56 dB	-53 / -55 dB	-52 / -54 dB
Audio Distortion ²	0.90%	0.90%	0.90%	0.90%	0.90%

BATTERIES						
Part No	Type	Capacity	HazLoc	Dimensions	Weight	Availability
PMNN4547	Li-Ion IMPRES 2	3100 mAh	Y	3.4 x 2.3 x 1.8 in (86 x 59 x 45 mm)	7.1 oz (201 g)	Standard

¹Please refer to local regulations for available channel bandwidths.
²Measured conductively in analog mode per TIA / EIA 603 under nominal conditions.
³Measured conductively in digital mode per TIA / EIA IS 102.



Encryption	
Supported Encryption Algorithms	ADP, AES, DES, DES-XL, DES-OFB, DVP-XL, Localized Algorithm
Encryption Algorithm Capacity	8
Encryption Keys per Radio	1024 keys Programmable for 128 Common Key References (CKR) or 16 Physical Identifiers (PID)
Encryption Frame Re-sync Interval	360 ms (P25 CAI)
Encryption Keying	Local Key Loader and Over the Air Rekeying (OTAR)
Synchronization	XL – Counter Addressing OFB – Output Feedback
Vector Generator	National Institute of Standards and Technology (NIST) approved random number generator
Encryption Type	Digital and SecureNet
Key Storage	Tamper-protected volatile or non-volatile memory
Key Erasure	Keyboard command and tamper detection
Standards	FIPS 140-2 Level 3 FIPS 197

GPS	
Constellations	GPS and GLONASS
Tracking Sensitivity	-164 dBm
Accuracy ¹	<5 meters (95%)
Cold Start ¹	<60 seconds (95%)
Hot Start ¹	<5 seconds (95%)
Mode of Operation	Autonomous (Non-Assisted)

Wireless	
Bluetooth®	
Frequency Range: 2402 - 2480 MHz	
Mission Critical Wireless Bluetooth 2.1 uses 96 bit encryption for pairing and 128 bit encryption for voice, signaling and data. The radio supports up to 6 data connections and 1 audio connection	
Bluetooth Low Energy uses 128-bit AES-CCM encryption	
WLAN	
Wi-Fi® 802.11 b/g/n	
Frequency Range: 2400 - 2483.5 MHz	
Supports WPA-2, WPA, WEP security protocols	
Radio can be pre-provisioned with up to 20 SSIDs	

Audio	
Audio Output at Rated	3 W
Audio Output at Max	5 W
Audio Response (EIA)	+1, -3 dB
Speech Loudness at 12 in (300 mm)	105 phon
Audio Features	Adaptive Equalization Adaptive Dual-sided Operation Adaptive Noise Suppression Intensity Adaptive Gain Control Adaptive Windporting IMPRES 2 Audio

Housing Color	
Housing Color	High Impact Green only

Regulatory Information		
FCC ID	All-Band	FCC ID: AZ489FT7111
IC ID	All-Band	IC ID: 109U-89FT7111
Emission Designators	LMR	8K10F1D, 8K10F1E, 8K10F1W, 11K0F3E, 16K0F3E, 20K0F1E
	Bluetooth	852KF1D, 1M17F1D, 1M19F1D
	WLAN (Wi-Fi)	13M7G1D, 17MOD1D, 18M1D1D

Environmental	
Operating Temperature ³	-20 to +60 °C (-20 to +140 °F)
Storage Temperature ¹	-40 to +85 °C (-40 to +185 °F)
Humidity	Per MIL-STD 810
ESD	IEC 801 - 2 kV
Dust Resistance	IP6X
Water Resistance	MIL-STD (Delta-T) and IPX8 (2 meters, 4 hours)
Leakage (Immersion)	MIL-STD-810 C, D, E, F and G

MIL-STD										
	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G	
	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
High Temperature	501.1	I,II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.5	I/A1, II/A1
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I/C3, II/C1
Temperature Shock	503.1	I	503.2	I/A1/C3	503.3	I/A1/C3	503.4	I	503.5	I-C
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I	505.5	I/A1
Rain	506.1	I,II	506.2	I,II	506.3	I,II	506.4	I,III	506.5	I,III
Humidity	507.1	II	507.2	II	507.3	II	507.4	1 Proc	507.5	II/Aggravated
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	1 Proc	509.5	1 Proc
Blowing Dust	510.1	I	510.2	I	510.3	I	510.4	I	510.5	I
Explosive Atmosphere	-	-	511.2	I	511.3	I	511.4	I	511.5/6	I
Blowing Sand	1 Proc	1 Proc	510.2	II	510.3	II	510.4	II	510.5	II
Submersion ²	512.1	I	512.2	I	512.3	I	512.4	I	512.5	I
Submersion (Salt Water) ²	512.1	I	512.2	I	512.3	I	512.4	I	512.5	I
Vibration	514.2	VIII,F, Curve-W	514.3	I/10, II/3	514.4	I/10, III/3	514.5	I/24, II/5	514.6	I/24, II/5
Shock	516.2	I, V	516.3	I, VI	516.4	I, VI	516.5	I, VI	516.6	I, VI
Shock (Drop)	516.2	II	516.2	IV	516.4	IV	516.5	IV	516.6	IV

¹ Measured conductively with >6 satellites visible at a nominal -130 dBm signal strength. Specs provided are 95th percentile values.

³ Radio only. To ensure best performance, batteries should be stored at 25 °C, ±5 °C .

² Submersion tests conducted using more stringent, preheated (Delta-T) method..

³ HazLoc certification requires an operating temperature of -20C to +60C.



ACHIEVE MISSION CRITICAL PERFORMANCE WITH MANAGED AND SUPPORT SERVICES

RISK & RESPONSIBILITY



ENSURE CONTINUITY • ENHANCE PRODUCTIVITY • REDUCE RISK.

ESSENTIAL

Only Support When You Need It

When the unpredictable happens to your network, Essential Services provide you access to Motorola's Technical Support teams and resources for troubleshooting and maintenance.

ADVANCED

Improve Response and Continuity

Motorola's expert service teams help mitigate downtime and ensure network continuity. Get fast response to network issues by our qualified technicians who analyze and diagnose your network as well as deliver routine maintenance.

PREMIER

Maximize Performance and Reduce Risk

Motorola's Managed Services team helps operate and optimize your mission critical system. With Premier Services, you fully transfer the risk to Motorola and ensure your system operates at maximum performance levels, allowing your team to keep focus on its primary responsibilities.

For more information, please visit: www.motorolasolutions.com/apx



MOTOROLA SOLUTIONS

Motorola Solutions Singapore Pte Ltd

80 Pasir Panjang Road #18-81 Mapletree Business City Singapore 117372

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2018 Motorola Solutions, Inc. All rights reserved. 07-2018