

# CB SERIES CALL BOXES

## YES, WE'RE HERE!

WITH A PUSH OF A BUTTON, CUSTOMERS CAN REACH YOUR STAFF, KNOWING IMMEDIATELY THAT HELP IS ON THE WAY.



### GENERAL SPECIFICATIONS

Model Number	CBM0010MKKAA	CBU0010MKKAA
Frequency	MURS	UHF
Frequency Range	151-154 MHz	452-470 MHz
Channel Capacity	1	
Channel Bandwidth	11.25kHz, 20kHz	12.5 kHz, 25 kHz *
Range Coverage	Up to 130,000 ft <sup>2</sup> in Retail Coverage	
PL Code	38	
DPL Code	83	
Dimensions (H x W x D)	7.5 in x 4.3 in x 1.2 in (190 mm x 110 mm x 30 mm)	
Weight with: Standard Alkaline Battery	454 g (1lb)	

\* Only for Canada

### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-30° C to +60° C
Storage Temperature	-40° C to +80° C

### ENERGY SPECIFICATIONS

Battery Type	AA Batteries
Quantity Needed	6
Battery Life <sup>1</sup>	1 Year
Operating Voltage	4.0 V

1. Battery life is based on an average of 7 uses per day.

### TRANSMITTER SPECIFICATIONS

Frequency	MURS	UHF
RF Output	345 mW	300 mW
Frequency Stability	+/- 2.0 ppm	+/- 2.5 ppm
Spurs and Harmonics	≤-20 dBm	≤-25 dBm
Modulation Limiting	±2.5 kHz @ 12.5 kHz	
Audio Frequency Response (1kHz)	0 dB	



Motorola Solutions, Inc. 500 West Monroe Street, Chicago, IL 60661 U.S.A. [motorolasolutions.com](http://motorolasolutions.com)

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2018 Motorola Solutions, Inc. All rights reserved. 03-2018