

COMPASS JOYSTICK

SPECIFICALLY DESIGNED FOR CRITICAL SECURITY INSTALLATIONS



- 27 tactile push buttons
- USB 2.0 HID compliant
- Jog / shuttle dial

GENERAL SPECIFICATIONS

MECHANICAL	
Dimensions	Height: 110.74 mm (4.36") Width: 228.35 mm (8.99") Depth: 279.40 mm (11.0")
Weight	1.13 kg (2.9lbs.)
Operating Force	2.8 N (0.63 lbf)
Maximum Vertical Load	200 N (45 lbf)
Maximum Horizontal Load	200 N (45 lbf)
Joystick Mechanical Angle of Movement	36° X & Y axis, 80° Z axis
Jog/Shuttle Performance Spring Loaded Ring Travel	±40°
Knob Rotation	360°
Expected Mechanical Life	3 million lifecycles
Lever Action (centering)	Spring
MATERIALS	
Body	ABS
Shaft	Stainless steel
Boot	Silicone
Handle	Glass filled nylon
ELECTRICAL / ENVIROMENTAL	
Operating Temperature	25 °C to +85 °C (-13 °F to +185 °F)
Storage Temperature	-25 °C to +85 °C (-13 °F to +185 °F)
Operating Humidity	20% to 80% (non-condensing)
Sealing	None
Regulatory	EMC Immunity Level: CE compliant, EMC directive 2004/108/EC, FCC Part 15 Subpart B
ORDERING DETAILS	
Product Code	110070

Note: Specifications are correct at the datasheet date of issue and are subject to change without prior notice.

For more information, please visit www.motorolasolutions.com/compass



