



# MOTOTRBO R7

## PORTABLE TWO-WAY RADIOS

MOTOTRBO™ R7 is a digital portable two-way radio that offers loud, clear, and customisable audio in a rugged, dependable, and connected device. Its advanced audio processing ensures that your voice is always understood, while the rugged construction is ready for the toughest environments.



### KEY FEATURES

- UHF/VHF/350MHz
- Digital/Analogue and 5-Tone support
- Wi-Fi 2.4/5.0 GHz
- WPA3 Wi-Fi security protocol compliant
- Bluetooth 5.2
- 2.4" 320 x 240 px. QVGA display
- Modern, intuitive user experience
- Full suite of accessories
- Sleek and ergonomic form factor
- Automatic Acoustic Feedback Suppression
- Adaptive Dual Microphone Noise Suppression
- Intelligent Audio
- IMPRES™ technology
- Programmable loudness up 107 phons
- Wideband speaker and microphones
- Simple audio configuration
- Up to 28 hours of battery life<sup>1</sup>
- IP68 (waterproof up to 2 metres for 2 hours)
- IP66 (concentrated water jet pressure)
- Intrinsically safe option (UL TIA-4950)
- Disinfectant and decontamination substance resistant housing<sup>2</sup>
- Robust and corrosion-proof side connector
- Rugged to MIL-STD 810



# SPECIFICATIONS

## GENERAL SPECIFICATIONS

R7 FULL KEYPAD MODEL (FKP)			R7 AND R7A NO KEYPAD MODEL (NKP)			
Band	UHF	350MHz	VHF	UHF	350MHz	VHF
Frequency	400-527 MHz	350-400 MHz	136-174 MHz	400-527 MHz	350-400 MHz <sup>a</sup>	136-174 MHz
High Power Output	4 W		5 W	4 W		5 W
Low Power Output	1 W					
Channel Spacing	12.5 kHz, 20 kHz <sup>b</sup> , 25 kHz					
Channel Capacity	1000 Channels			64 Channels		
Display	2.4" 320 x 240 px. QVGA display, with up to 10 lines of text			N/A		
Power Supply (Nominal)	7.5 V					

### MOTOTRBO R7 with 2200 mAh Slim IMPRES Li-Ion battery (PMNN4807)

Dimensions (H x W x D)	132 x 56 x 35 mm		132 x 56 x 31 mm		
Weight <sup>3</sup>	316 g		289 g		
Digital / Analogue Battery Life <sup>1</sup>	19 / 14.5 hrs	20 / 15 hrs	19 / 14.5 hrs	20 / 15 hrs	
Operating Temperature	-20 °C to 60 °C				

### MOTOTRBO R7 with 2450 mAh Li-Ion battery (PMNN4808)

Dimensions (H x W x D)	132 x 56 x 41 mm		132 x 56 x 37 mm		
Weight <sup>3</sup>	346 g		319 g		
Digital / Analogue Battery Life <sup>1</sup>	21.5 / 16.5 hrs	22 / 17 hrs	21.5 / 16.5 hrs	22 / 17 hrs	
Operating Temperature	-20 °C to 60 °C				

### MOTOTRBO R7 with 2850 mAh IMPRES Li-Ion battery (PMNN4809)

Dimensions (H x W x D)	132 x 56 x 35mm		132 x 56 x 31mm		
Weight <sup>3</sup>	333 g		306 g		
Digital / Analogue Battery Life <sup>1</sup>	25 / 19 hrs	26 / 19.5 hrs	25 / 19 hrs	26 / 19.5 hrs	
Operating Temperature	-20 °C to 60 °C				

### MOTOTRBO R7 with 3200 mAh HazLoc IMPRES Li-Ion battery (PMNN4810)

Dimensions (H x W x D)	132 x 56 x 41 mm		132 x 56 x 37 mm		
Weight <sup>3</sup>	366 g		339 g		
Digital / Analogue Battery Life <sup>1</sup>	28 / 21.5 hrs	29 / 22 hrs	28 / 21.5 hrs	29 / 22 hrs	
Operating Temperature	-20 °C to 60 °C				

# SPECIFICATIONS

## TRANSMITTER SPECIFICATIONS

Channel Spacing	12.5 kHz, 20 kHz, 25 kHz
4FSK Digital Modulation	<ul style="list-style-type: none"> <li>12.5 kHz Data Only: 7K60F1D &amp; 7K60FXD</li> <li>12.5 kHz Data &amp; Voice: 7K60F1E &amp; 7K60FXE</li> <li>Combination of 12.5 kHz Voice and Data: 7K60F1W</li> </ul>
Digital Protocol	<ul style="list-style-type: none"> <li>ETSI TS 102 361-1, -2, -3, -4</li> <li>DMR Tier II and DMR Tier III</li> </ul>
Conducted/Radiated Emissions (TIA603D)	<ul style="list-style-type: none"> <li>-36 dBm &lt; 1 GHz</li> <li>-30 dBm &gt; 1 GHz</li> </ul>
Adjacent Channel Power	<ul style="list-style-type: none"> <li>60 dB @ 12.5 kHz</li> <li>70 dB @ 20 kHz / 25 kHz</li> </ul>
Frequency Stability	+/-0.5 ppm

## RECEIVER SPECIFICATIONS

Analogue Sensitivity (12dB SINAD)	0.16 µV (typical)
Digital Sensitivity (5% BER)	0.14 µV (typical)
Intermodulation (TIA603D)	70 dB
Adjacent Channel Selectivity, (TIA603A)-1T	<ul style="list-style-type: none"> <li>60 dB @ 12.5 kHz</li> <li>70 dB @ 20 kHz / 25 kHz</li> </ul>
Adjacent Channel Selectivity, (TIA603D)-2T	<ul style="list-style-type: none"> <li>45 dB @ 12.5 kHz</li> <li>70 dB @ 20 kHz / 25 kHz</li> </ul>
Spurious Rejection (TIA603D)	70 dB

## GNSS SPECIFICATIONS

Constellation Support	GPS, GLONASS, BEIDOU, GALILEO
Time To First Fix, Cold Start	≤ 60 seconds
Time To First Fix, Hot Start	≤ 10 seconds
Horizontal Accuracy	< 5 metres

## WI-FI SPECIFICATIONS

Frequency Range	2.4 GHz, 5 GHz
Standards Supported	Wi-Fi 5 / IEEE 802.11a/b/g/n/ac
Security Protocol Supported	WPA-3, WPA-2
Maximum Number of SSIDs	128 (64 for NKP Models)

## HAZLOC CERTIFICATION

ANSI/UL TIA 4950 and CAN/CSA C22.2 No. 157-92 as intrinsically safe for use in Class I, II, III, Division 1, Groups C, D, E, F, G, Division 2, Groups A, B, C, D

## BLUETOOTH SPECIFICATIONS

Version	5.2
Range	Class 2, 10 m
Supported Profiles	Bluetooth Headset Profile (HSP), Serial Port Profile (SPP), Personal Area Network (PAN), Generic Attributes (GATT), In-door location (Bluetooth LE Passive Scanning)
Simultaneous Connections	1 audio accessory and up to 4 data devices

## AUDIO SPECIFICATIONS

Digital Vocoder Type	AMBE+2
Audio Response (TIA603D)	+1, -3 dB
Audio Output Power (Rated/Max)	1 W / 3 W
Audio Distortion at Rated Audio	≤1.5%
Maximum Speech Loudness by Default (ISO5326)	102 phon @ 30 cm
Maximum Programmable Speech Loudness (Extra Loud Mode, Level 3)	107 phon @ 30cm
Hum and Noise	<ul style="list-style-type: none"> <li>-40 dB @ 12.5 kHz</li> <li>-45 dB @ 20 kHz / 25 kHz</li> </ul>
Conducted Spurious Emissions (TIA603D)	-57 dBm

## ENVIRONMENTAL SPECIFICATIONS

Operating Temperature <sup>4</sup>	-30°C to 60°C
Storage Temperature	-40 °C to 85 °C
Thermal Shock	Per MIL-STD
Humidity	Per MIL-STD
Electrostatic Discharge	IEC 61000-4-2 Level 4
Dust and Water Intrusion	IP68 (submersion up to 2m, 2hrs) IP66 for high pressure-water resistance per IEC 60529
Salt Fog	5% NaCl for 8 hrs at 35 °C, 16 hrs standing
Packaging Test	MIL-STD 810D and E

## MILITARY STANDARDS (MIL-STD 810)

	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G		MIL-STD 810H	
	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.6	II	500.6	II
High Temp	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.6	I/A1, II/A1	501.7	I/A1, II/A1
Low Temp	502.1	I	502.2	I, II	502.3	I, II	502.4	I, II	502.6	I, II	502.7	I, II
Temp Shock	503.1	I	503.2	A1/C3	503.3	A1/C3	503.4	I	503.6	I-C	503.7	I-C
Solar Radiation	-	II	505.2	I/A1	505.3	I/A1	505.4	I/A1	505.6	I/A1	505.7	I/A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.6	I, III	506.6	I, III
Humidity	507.1	II	507.2	II	507.3	II	507.4	-	507.6	II/Aggravated	507.6	II/Aggravated
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	-	509.6	-	509.7	-
Blowing Dust & Sand	510.1	I/-	510.2	I, II	510.3	I, II	510.4	I, II	510.6	I, II	510.7	I, II
Vibration	514.2	VIII/CatF, XI	514.3	I/Cat10, II/Cat3	514.4	I/Cat10, III/Cat3	514.5	I/Cat24, II/Cat5	514.7	I/Cat24, II/Cat5	514.8	I/Cat24, II/Cat5
Shock	516.2	I, II	516.3	I, IV	516.4	I, IV	516.5	I, IV	516.7	I, IV	516.8	I, IV
Contamination by Fluids									504.2	II	504.3	2.2.6 b

# FEATURE COMPATIBILITY

	R7 FKP	R7 NKP	R7a
<b>GENERAL</b>			
UHF and 350MHz 4 W, VHF 5 W	•	•	•
Full Keypad	•	—	—
Colour Screen	•	—	—
Analogue and Digital	•	•	•
Voice and Data	•	•	•
Integrated Wi-Fi	○	○	—
Canned Text Messaging	•	•	•
Freeform Text Messaging	•	—	—
Text to Speech	•	•	•
Work Order Ticketing	•	—	—
Indoor Location Tracking	○	○	—
Event-Driven Location Update	○	○	—
Outdoor Location Tracking	○	○	—
Bluetooth Audio	○	○	—
Bluetooth Data	○	○	—
Voice Announcement	•	•	•
Home Channel Reminder	•	•	•
Late Entry	•	•	•
Priority Scan	•	•	•
Real-Time Clock	•	•	—
Audio Recording/Playback	○	○	—
Secure Linux Operating System	•	•	•
M-Radio Control App	○	○	—
<b>AUDIO</b>			
Intelligent Audio in Analogue and Digital	•	•	•
IMPRES Audio	•	•	•
Automatic Acoustic Feedback Suppressor	•	•	•
Microphone Distortion Control	•	•	•
User-Selectable Audio Profile	•	•	•
Trill Enhancement	•	•	•
Advanced Dual Microphone Noise Suppression <sup>6</sup>	•	•	—
Single Microphone Noise Cancellation	—	—	•
<b>SYSTEMS</b>			
Dual Capacity Direct Mode	•	•	•
Conventional	•	•	•
IP Site Connect	•	•	•
Capacity Plus Single/Multi Site	•	•	•
Capacity Max	○	○	○

	R7 FKP	R7 NKP	R7a
<b>MANAGEMENT</b>			
CPS 2.0 and Radio Management	•	•	•
Over-the-Air Programming (via DMR)	•	•	•
Over-the-Air Software Update (via Wi-Fi)	○	○	—
IMPRES Energy	○	○	○
IMPRES Battery Management	○	○	○
Over-the-Air Battery Management	○	○	○
<b>SAFETY</b>			
Emergency Button	•	•	•
Man Down / Fall Alert	○	○	—
Lone Worker	•	•	•
IP68 (waterproof up to 2 metres for 2 hours)	•	•	•
IP66 (concentrated water jet pressure)	•	•	•
Rugged to MIL-STD 810	•	•	•
Disinfectant / Decontamination Resistant <sup>2</sup>	•	•	•
Sensor Integration	○	○	—
Integrated Accelerometer	•	•	—
Basic Privacy	•	•	• <sup>7</sup>
Enhanced Privacy	•	•	•
AES256 encryption	○	○	○
Transmit Interrupt	•	•	•
Digital Emergency	•	•	•
Emergency Search Tone	•	•	•
Remote Monitor	•	•	•
Radio Disable / Enable	•	•	•
Secure Processor	•	•	•
Digital Certificates	•	•	—
<b>CUSTOMISATION</b>			
GCAI-Mini Accessory Port	•	•	•
6 Programmable Buttons	•	—	—
4 Programmable Buttons	—	•	•
Day / Night Screen Mode	•	—	—
Action List	•	—	—
Label Recess	•	•	•
Option Board <sup>5</sup>	○	○	—

• Included ○ Optional — Not Included

<sup>1</sup>Typical battery life, 5/5/90 profile at maximum transmitter power with GNSS, Bluetooth, Wi-Fi and Option Board applications disabled. Actual observed runtimes may vary.

<sup>2</sup>Please refer to the MOTOTRBO R7 user manual for a list of approved disinfectants and decontamination substances.

<sup>3</sup>Radio weight information is exclusive of General Option Board and antenna.

<sup>4</sup>Please check battery specifications for more detail on battery operating temperature.

<sup>5</sup>Pending aftermarket option board installation.

<sup>6</sup>Noise suppression method differs between accessories.

<sup>7</sup>Basic privacy is not available for TIA-certified R7a but is included as standard on non-TIA R7a models.

<sup>8</sup>R7a does not support 350MHz band. R7 FKP and R7 NKP 350MHz models do not support 20kHz channel spacing.

For more information, please visit  
[motorolasolutions.com/R7](https://motorolasolutions.com/R7)

Motorola Solutions UK Ltd, Nova South, 160 Victoria Street, London, SW1E 5LB, United Kingdom.

Availability is subject to individual country law and regulations. All specifications shown are typical unless otherwise stated and are subject to change without notice.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2023 Motorola Solutions, Inc. All rights reserved. (08-23)